


City of Hilshire Village, Texas

Hickory Shadows Drive

Paving, Drainage & Water Line Improvements

June, 2025

100% Submittal



City of Hilshire Village

VICINITY MAP

NOT TO SCALE
HARRIS COUNTY KEY MAP 491B



MAYOR

Robert (Bob) Buesinger

COUNCIL

Mike Gordy

Andy Carey

Kristi Cooper

Justin Crawford

Mark Huber

CITY SECRETARY

Cassie Stephens

SHEET SHEET TITLE No.

GENERAL

- | | |
|-----|------------------------------------|
| 01 | COVER SHEET |
| 02 | GENERAL CONSTRUCTION NOTES |
| 03 | LEGEND & ABBREVIATIONS |
| 04 | SURVEY CONTROL MAP OVERALL |
| 04A | SURVEY CONTROL DETAILS |
| 05 | OVERALL LAYOUT |
| 06 | DRAINAGE AREA MAP AND CALCULATIONS |

TRAFFIC CONTROL PLAN

- | | |
|----|--|
| 07 | TRAFFIC CONTROL PLAN - GENERAL NOTES |
| 08 | HICKORY SHADOWS DRIVE TRAFFIC CONTROL PLAN - PHASE I & 2 |
| 09 | HICKORY SHADOWS DRIVE TRAFFIC CONTROL PLAN - PHASE 3 |
| 10 | ONE LANE TWO-WAY TRAFFIC CONTROL DETAIL |
| 11 | TYPICAL TRAFFIC CONTROL DETAILS |

PLAN & PROFILE

- | | | |
|----|---|-----------------------|
| 12 | HICKORY SHADOWS DRIVE (PAVING & DRAINAGE) | STA 1+00 TO STA 2+75 |
| 13 | HICKORY SHADOWS DRIVE (PAVING & DRAINAGE) | STA 2+75 TO STA 7+75 |
| 14 | HICKORY SHADOWS DRIVE (PAVING & DRAINAGE) | STA 7+75 TO STA 10+50 |
| 15 | HICKORY SHADOWS DRIVE (WATER LINE) | STA 1+00 TO STA 2+75 |
| 16 | HICKORY SHADOWS DRIVE (WATER LINE) | STA 2+75 TO STA 7+75 |
| 17 | HICKORY SHADOWS DRIVE (WATER LINE) | STA 7+75 TO STA 10+50 |
| 18 | HICKORY SHADOWS DRIVE (WATER LINE EASEMENT) | STA 1+00 TO STA 5+13 |

STORM WATER POLLUTION PREVENTION PLAN

- | | |
|----|--|
| 19 | STORM WATER POLLUTION PREVENTION PLAN |
| 20 | STORM WATER POLLUTION PREVENTION DETAILS I |

CONSTRUCTION DETAILS

- | | |
|----|------------------------|
| 21 | PAVING DETAILS I |
| 22 | PAVING DETAILS II |
| 23 | STORM SEWER DETAILS I |
| 24 | STORM SEWER DETAILS II |
| 25 | WATER DETAILS I |
| 26 | WATER DETAILS II |

TREE PROTECTION PLAN

- | | |
|----|-------------------------------------|
| 27 | TREE PROTECTION PLAN (SHEET 1 OF 2) |
| 28 | TREE PROTECTION PLAN (SHEET 2 OF 2) |



SUBMITTED BY: _____ DATE: _____
NGOC KIM LE, PE
HDR ENGINEERING, INC

APPROVED BY: _____ DATE: _____
ROBERT (BOB) BUESINGER
MAYOR, CITY OF HILSHIRE VILLAGE



HDR Engineering Inc. Texas Reg. No. 754
4828 Loop Central Drive, Suite 700 • Houston, Texas 77081
(713) 622-9264 • Fax (713) 622-9265 • www.hdrinc.com

HDR PROJECT NO. 10418041

1. CONTRACTOR SHALL NOTIFY THE CITY OF HILSHIRE VILLAGE AT (713) 973-1779 AND THE ENGINEER AT (713) 622-9264 48 HOURS PRIOR TO START OF CONSTRUCTION.
2. CONTRACTOR SHALL CONTACT ALL PERTINENT UTILITY COMPANIES 48 HOURS (MINIMUM) PRIOR TO EXCAVATION IN AREA. THE HOUSTON AREA UTILITY COORDINATING COMMITTEE MAY BE CONTACTED FOR CERTAIN UTILITIES AT (713) 223-4567 OR TOLL FREE 1-800-669-8344 48 HOURS BEFORE BEGINNING WORK.
3. CONTRACTOR SHALL COORDINATE ANY UTILITY CONSTRUCTION THAT MAY DISRUPT SERVICE WITH THE CITY OF HILSHIRE VILLAGE (CASSIE STEPHENS, CITY SECRETARY, 713-973-1779.) AND THE CITY'S OPERATOR (ST SERVICES @ 281-578-4200). NOTIFY CITY 24 HOURS IN ADVANCE.
4. PROPERTY OWNERS SHALL BE NOTIFIED IN WRITING BY THE CONTRACTOR, BETWEEN 48 HOURS AND 7 DAYS IN ADVANCE OF DISTURBANCE OF DRIVEWAYS. PROPERTY OWNER SHALL BE PROVIDED THE MINIMUM FOLLOWING INFORMATION: WORK TO BE PERFORMED, STARTING AND ENDING DATES, THE NAME AND NUMBER OF CONTRACTOR'S REPRESENTATIVE, AND NAME OF HILSHIRE VILLAGE OFFICIAL TO BE CONTACTED FOR QUESTIONS. WRITTEN NOTICES SHALL BE APPROVED BY HILSHIRE VILLAGE PRIOR TO DISTRIBUTION.
5. TEXAS LAW ARTICLE 1436C, PROHIBITS ALL ACTIVITIES IN WHICH PERSONS OR EQUIPMENT MAY COME WITHIN SIX FEET OF ENERGIZED OVERHEAD POWER LINES, AND FEDERAL REGULATIONS, TITLE 29, PART 1910.180(I) AND PART 1926.550(A)(15) REQUIRE A MINIMUM CLEARANCE OF TEN FEET FROM THESE FACILITIES. THE ABOVE LAWS CARRY BOTH CRIMINAL AND CIVIL LIABILITIES, WITH CONTRACTORS AND OWNERS BEING LEGALLY RESPONSIBLE FOR THE SAFETY OF WORKERS UNDER THESE LAWS. IF YOU OR YOUR COMPANY MUST WORK NEAR OVERHEAD POWER LINES, CALL (713) 228-7400 FOR THE LINES TO BE DE-ENERGIZED AND/OR MOVED AT YOUR EXPENSE.
6. IN THE EVENT A GAS LINE IS EXPOSED DUE TO EXCAVATION AND IS IN NEED OF RELOCATION, THE APPROPRIATE GAS COMPANY SHALL BE CONTACTED BY THE CONTRACTOR TO HAVE STATUS OF THE LINE VERIFIED. CONTRACTOR IS RESPONSIBLE FOR HAVING THE GAS COMPANY RELOCATE THE GAS LINES WITHIN THE RIGHT OF WAY. SEE NOTE FOR CENTERPOINT ENERGY THIS PAGE.
7. THE PREPARATION OF THESE PLANS REFLECT INFORMATION PROVIDED BY OTHERS ON THE APPROXIMATE LOCATION AND EXISTENCE OF EXISTING UTILITIES AND ADJACENT PHYSICAL FEATURES; HOWEVER, THEY DO NOT IMPLY OR AFFIRM THAT ALL UTILITIES OR PHYSICAL FEATURES ARE SHOWN. GENERALLY, UTILITY SERVICE CONNECTIONS ARE NOT INDICATED ON THESE PLANS. CONTRACTOR IS RESPONSIBLE FOR NOTIFICATION OF THE OWNER IMMEDIATELY UPON ENCOUNTERING UNFORESEEN CONFLICTS.
8. IT IS THE CONTRACTOR'S RESPONSIBILITY TO DETERMINE THE DEPTH, LOCATION AND EXISTENCE OF ALL EXISTING UTILITIES WHICH MAY CONFLICT WITH THE PROPOSED CONSTRUCTION, PRIOR TO CONSTRUCTION. NOTIFY ENGINEER OF ANY DISCREPANCIES.
9. RIGHTS OF WAY INDICATED ARE APPROXIMATE. CONTRACTOR SHALL VERIFY EXACT LIMITS OF RIGHT OF WAY PRIOR TO CONSTRUCTION.
10. THE CONTRACTOR SHALL MAINTAIN ACCESS TO RESIDENTIAL AND COMMERCIAL PROPERTIES ADJACENT TO WORK AREAS AT ALL TIMES.
11. NO EXCAVATIONS SHALL BE LEFT OPEN OVERNIGHT. ALL EXCAVATIONS WHICH CANNOT BE BACKFILLED OVERNIGHT SHALL BE COVERED. USE STEEL PLATES WHEN IN PAVED AREAS; IN OTHER AREAS USE 3/4" PLYWOOD, WOOD PLANKING OR OTHER MATERIAL APPROVED BY THE CITY. THE EXCAVATION AREA MUST BE WELL PROTECTED WITH TRAFFIC BARRICADES EQUIPPED WITH FLASHING YELLOW LIGHTS, DURING ACTIVE CONSTRUCTION PERIODS. THE EXCAVATION AREAS MUST BE COMPLETELY CORDONED OFF WITH PLASTIC TAPE OR CONSTRUCTION FENCE WHEN CONSTRUCTION IS NOT ACTIVELY PROGRESSING.
12. THE CONTRACTOR SHALL CONDUCT HIS OPERATIONS IN A MANNER SUCH THAT TRUCKS AND OTHER VEHICLES DO NOT CREATE A DIRT NUISANCE OR SAFETY HAZARD IN ANY STREETS, PUBLIC OR PRIVATE. CLEAN UP OF STREETS SHALL BE DONE DAILY.
13. IT IS IMPERATIVE THAT THE CONSTRUCTION IN THE PROJECT AREA INCONVENIENCE THE RESIDENTS OF THE AREA AS LITTLE AS POSSIBLE. CLEAN-UP SHALL BE COMPLETED AND MAINTAINED WITHIN ONE BLOCK BEHIND ALL CONSTRUCTION OF UTILITIES AND PAVING. CLEAN-UP INCLUDES COMPACTION OF BACKFILL, CLOSURE OF BORE PITS, AND SURFACE RESTORATION. NEW CONSTRUCTION OPERATIONS TO BE SUSPENDED TEMPORARILY IF COMPLETE CLEAN-UP IS FURTHER THAN ONE BLOCK BEHIND CONSTRUCTION.
14. ANY AREA OF GRASS WHICH IS DISTURBED OR DUG UP DURING THE CONSTRUCTION SHALL BE REPLACED WITH ST. AUGUSTINE SOD OR GRASS WHICH MATCHES THE GRASS REMOVED, AT NO ADDITIONAL COST TO THE CITY. WHEN CONSTRUCTION OCCURS IN CITY RIGHTS-OF-WAY AND EASEMENTS ON RESIDENTIAL YARD AREAS, CARE SHALL BE TAKEN TO MINIMIZE CONSTRUCTION DAMAGE TO YARD AREAS.
15. CONTRACTOR SHALL ADEQUATELY PROTECT EXISTING STRUCTURES, SPRINKLER SYSTEMS, LANDSCAPING, UTILITIES, POWER POLES, TREES, SHRUBS AND OTHER PERMANENT OBJECTS. TREES SHALL NOT BE REMOVED OR DISTURBED UNLESS OTHERWISE NOTED IN THE TREE PROTECTION PLANS. WHERE TREE ROOTS MUST BE CUT, FOLLOW THE REPAIR METHODS DESCRIBED IN THE SPECIFICATIONS AND TREE PROTECTION PLANS. ALL COST FOR REPAIRS OR REPLACEMENT OF DAMAGE DUE TO CONTRACTOR'S PERFORMANCE WILL BE PAID BY THE CONTRACTOR AT NO ADDITIONAL COST TO THE PROJECT.
16. CONTRACTOR SHALL NOT USE RESIDENTS WATER.
17. PROGRESS MEETINGS WILL BE HELD BETWEEN THE CONTRACTOR, THE CITY, AND THE ENGINEER ON A MONTHLY BASIS DURING CONSTRUCTION, AND MORE FREQUENTLY IF NEEDED.

1. THE CONTRACTOR'S SURVEYOR SHALL BE REGISTERED IN THE STATE OF TEXAS AND SHALL VERIFY THE LOCATION OF THE RIGHT OF WAY AND BASELINE PRIOR TO CONSTRUCTION.
2. RELOCATE ALL EXISTING PRIVATE UTILITIES AS NECESSARY FOR CONSTRUCTION. LOCATION AND ELEVATIONS OF EXISTING UTILITIES SHOWN ON DRAWINGS ARE APPROXIMATE AND SHALL BE VERIFIED BY THE CONTRACTOR PRIOR TO CONSTRUCTION. RELOCATION OF EXISTING UTILITIES SHALL BE AT THE CONTRACTOR'S EXPENSE.
3. PROVIDE ONE FOOT (1') MINIMUM CLEARANCE BETWEEN GAS LINES AND OTHER UTILITIES (NEW OR EXISTING).
4. CONTRACTOR SHALL COMPLY WITH OSHA REGULATIONS AND STATE OF TEXAS LAW CONCERNING EXCAVATION, TRENCHING AND SHORING.
5. CONTRACTOR SHALL MAINTAIN ADEQUATE DRAINAGE AT ALL TIMES DURING CONSTRUCTION AND SHALL RESHAPE AND REGRADE STREET DITCH TO ORIGINAL OR BETTER CONDITION, IF DISTURBED DURING CONSTRUCTION, AT NO ADDITIONAL COST TO THE CITY.
6. ALL EXCAVATION AREAS MUST BE COMPLETELY CORDONED OFF WITH A MINIMUM OF TWO STRANDS OF PLASTIC CONSTRUCTION TAPE, OR CONSTRUCTION FENCE ACCEPTABLE TO THE CITY. ADEQUATE BARRICADES WITH FLASHING YELLOW LIGHTS SHALL BE INSTALLED TO PROTECT PEDESTRIAN AND VEHICLE TRAFFIC.
7. ALL PAVEMENTS OUTSIDE THE PROJECT AREA REMOVED OR DAMAGED DURING CONSTRUCTION SHALL BE REPLACED WITH EQUAL OR BETTER MATERIALS, TO THE SATISFACTION OF THE ENGINEER, AT NO ADDITIONAL COST TO THE CITY.
8. UNIT PRICE ITEM FOR REMOVAL AND REPLACEMENT OF EXISTING DRIVEWAYS SHALL INCLUDE THE REPLACEMENT OF DRIVEWAYS USING EITHER PLAIN REINFORCED CONCRETE OR ASPHALT, BASED ON THE TYPE OF MATERIAL THE EXISTING DRIVEWAY IS MADE OF. REMOVE AND REPLACE EXISTING DRIVEWAYS IN ACCORDANCE WITH THE FOLLOWING SCHEDULE:

Existing Driveway Material	Proposed Driveway Material
Concrete	Concrete
Concrete with decorative paving materials	Concrete
Concrete with asphalt overlay	Concrete
Asphalt	Asphalt
Asphalt with decorative paving materials	Asphalt
Gravel/Other	Asphalt
9. DECORATIVE DRIVEWAYS AND SIDEWALKS EXIST WITHIN THE PROJECT AREA LIMITS. CONTRACTOR SHALL COORDINATE AND GIVE THE OPPORTUNITY TO PROPERTY OWNERS TO PAY THE DIFFERENCE IN COST FOR THE REPLACEMENT/UPGRADE OF ANY DECORATIVE MATERIALS OR TREATMENTS USED ON THEIR DRIVEWAYS AND/OR SIDEWALKS. PAYMENT FOR THE UPGRADE IN MATERIALS SHALL BE MADE BY THE HOMEOWNER DIRECTLY TO THE CONTRACTOR, WITH THE CITY'S ONLY INVOLVEMENT BEING TO FACILITATE DISPUTE RESOLUTION.
10. DRIVEWAY AND SIDEWALK REPLACEMENT SHALL MATCH THE WIDTH AND LOCATION OF THE EXISTING FACILITY.
11. PARKING AREAS BUILT WITHIN STREET RIGHTS-OF-WAY SHALL BE REMOVED AS SHOWN ON THE PLANS AND IN ACCORDANCE WITH SECTION 02100 - RIGHT OF WAY PREPARATION. COST TO REMOVE THESE FACILITIES IS INCIDENTAL TO THE PROJECT, UNLESS OTHERWISE NOTED IN THE BID FORM. RECONSTRUCTION OF THESE PARKING AREAS IS NOT INCLUDED UNDER THIS CONTRACT.
12. LARGE MASONRY MAILBOXES AND OTHER TYPES OF DECORATIVE MAILBOXES EXIST WITHIN THE PROJECT AREA LIMITS. CONTRACTOR SHALL TEMPORARILY REMOVE AND RELOCATE ANY MAILBOXES LOCATED WITHIN THE STREET RIGHT-OF-WAY OUT OF HARMS WAY. CONTRACTOR SHALL COORDINATE WITH PROPERTY OWNERS AND ENGINEER FOR THE TEMPORARY AND PERMANENT RELOCATION OF THESE FACILITIES. COST FOR TEMPORARY AND PERMANENT RELOCATION OF MAILBOXES IS INCIDENTAL TO THE PROJECT, UNLESS OTHERWISE NOTED IN THE BID FORM.
13. THE RESIDENTS AT 1 HICKORY SHADOWS REQUIRE CONTINUOUS ACCESS TO THEIR DRIVEWAY AND HOME. CONTRACTOR SHALL PROVIDE CONSTANT ACCESS TO DRIVEWAY THROUGHOUT THE ENTIRETY OF PROJECT DURATION AS NOTED IN PLANS.

- All proposed facilities shall maintain 12" clear from all existing utilities.

MK.	DESCRIPTION	DATE	DWN.	CHK.



HDR Engineering Inc. Texas Reg. No. 754
4828 Loop Central Drive, Suite 700 • Houston, Texas 77081
(713) 622-9264 • Fax (713) 622-9265 • www.hdrinc.com

Job No.: 10418041

Job No.: 10418041

Date: June, 2025

Dwn By: G.S. Fuller

Scale: 1000'










HURZ :
VERT :

ONE INCH

IF ABOVE MARK DOES NOT
MEASURE ONE INCH, THEN

THIS DWG. NOT TO SCALE

SYMBOL	DESCRIPTION
	IRON PIPE OR IRON ROD MONUMENTS
	CENTERLINE OF RIGHT-OF-WAY
	SURVEY BASELINE
	EXISTING RIGHT-OF-WAY LINE
	PROPERTY LINE
	DIMENSION LINE
	CURB LINE
	EDGE OF ASPHALT PAVEMENT
	SIDEWALK
	SHRUBS
	TREE
	BUILDING
	SLAB
	POST, WOOD OR METAL
	INDEX CONTOUR
	WATER LINE (20" & SMALLER)
	WATER LINE (24" & LARGER)
	WATER VALVE (GATE OR BUTTERFLY)
	TAPPING SLEEVE AND VALVE
	FIRE HYDRANT
	WATER METER
	GAS LINE
	GAS METER
	SANITARY SEWER LINE (24" & SMALLER)
	SANITARY SEWER LINE (30" & LARGER)
	SANITARY SEWER LINE, MANHOLE & CLEANOUT
	STORM SEWER LINE (24" & SMALLER)
	STORM SEWER LINE (30" & LARGER)
	STORM SEWER LINE AND MANHOLE
	STORM SEWER JUNCTION BOX
	CURB INLET
	GRATE INLET
	CONCRETE DRAIN
	CULVERT
	SOUTHWESTERN BELL MANHOLE & OVERHEAD & BURIED CABLE
	TELEPHONE BOX
	STREET LIGHT (CANTILEVERED ON WOODEN POLE)
	STREET LIGHT (CANTILEVERED ON ORNAMENTAL POLE)

<u>SYMBOL</u>	<u>DESCRIPTION</u>
	HOUSTON LIGHTING & POWER CO CONDUIT & MANHOLE
	POWER POLE W/OVERHEAD LINES
	POWER POLE W/DOWN GUY
	TRAFFIC LIGHT POLE
	MARKER
	BUSINESS SIGN
	SIGN POST
	FENCE LINE (CHAIN LINK OR OTHER)
	FENCE LINE (BARBED WIRE)

<u>SYMBOL</u>	<u>DESCRIPTION</u>
	NORTH OR EAST RIGHT-OF-WAY
	SOUTH OR WEST RIGHT-OF-WAY
	NORTH OR EAST DITCH OR CURB
	SOUTH OR WEST DITCH OR CURB
	CENTER LINE OF PAVEMENT
	RELIANT ENERGY CONDUIT
	GAS LINE
	SOUTHWESTERN BELL COMMUNICATION CONDUIT
	WATER LINE (20" & SMALLER)
	WATER LINE (24" & LARGER)
	SANITARY SEWER LINE (24" & SMALLER)
	SANITARY SEWER LINE (30" & LARGER)
	STORM SEWER LINE (24" & SMALLER)
	STORM SEWER LINE (30" & LARGER)
	RELIANT ENERGY MANHOLE
	SOUTHWESTERN BELL TELEPHONE MANHOLE
	SANITARY SEWER MANHOLE & CLEANOUT
	STORM SEWER MANHOLE

<u>SYMBOL</u>	<u>DESCRIPTION</u>
	BORING LOCATION
	POINT OF INTERSECTION (PI)
	POINT OF CURVE (PC) OR POINT OF TANGENCY (PT)
	WATER LINE (20" & SMALLER)
	WATER LINE (24" & LARGER)
	TAPPING SLEEVE & VALVE
	FIRE HYDRANT
	SANITARY SEWER LINE (24" & SMALLER)
	SANITARY SEWER LINE (30" & LARGER)
	SANITARY SEWER MANHOLE
	STORM SEWER LINE (24" & SMALLER)
	STORM SEWER LINE (30" & LARGER)
	STORM SEWER MANHOLE
	CURB INLET
	FACE OF CURB
	PROPOSED SIGN
	CONCRETE WALK

<u>SYMBOL</u>	<u>DESCRIPTION</u>
	WATER LINE (20" & SMALLER)
	WATER LINE (24" & LARGER)
	SANITARY SEWER LINE (24" & SMALLER)
	SANITARY SEWER LINE (30" & LARGER)
	STORM SEWER LINE (24" & SMALLER)
	STORM SEWER LINE (30" & LARGER)
	PVC SLEEVE
	SANITARY SEWER MANHOLE
	STORM SEWER MANHOLE
	STORM SEWER INLET
	TOP OF CURB OR CENTERLINE OF OPEN DITCH PAVING


& ⊙ AB AC AVE	AND AT ALL BELL ASBESTOS CEMENT AVENUE	RJ RT RW S SAN SPL SPRINK ST STA STD STL STM SWR SWBT	RESTRAINED JOINT RIGHT RETAINING WALL SOUTH SANITARY SPECIAL SPRINKLER STREET STATION ALONG BASELINE OR CENTERLINE STANDARD STEEL STORM SEWER SOUTHWESTERN BELL COMMUNICATION COMPANY
Ⓡ B-B BC BSSN	BASELINE BACK TO BACK BEHIND CURB BUSINESS SIGN	T TBM TOC OR TC TEMP TP TS & V TY TYP	TANGENT TEMPORARY BENCH MARK TOP OF CURB TEMPORARY TOP OF PAVEMENT TAPPING SLEEVE AND VALVE TYPE TYPICAL
CI Ⓢ CLR CMP COH CONC CONSTR CPE CSG CTMS	CAST IRON CENTERLINE CLEAR CORRUGATED METAL PIPE CITY OF HOUSTON CONCRETE CONSTRUCTION CENTER POINT ENERGY CASING COMPUTERIZED TRANSPORTATION MANAGEMENT SYSTEM	UE UG VC W W/ WL WLE WM WP WV	UTILITY EASEMENT UNDERGROUND VERTICAL CURVE WEST WITH WATER LINE WATER LINE EASEMENT WATER METER WOOD POLE WATER VALVE
DI DIA DR DWG	DUCTILE IRON DIAMETER DRIVE DRAWING		
E EL OR ELEV EOP ESP E/R ESMT EXIST	EAST ELEVATION EDGE OF PAVEMENT EXTRA STRENGTH PIPE END OF CURB RETURN EASEMENT EXISTING		
FC F-F FH ? FT	FACE OF CURB FACE-TO-FACE FIRE HYDRANT FLOWLINE FEET		
GV & B	GATE VALVE AND BOX		
HL & P HMAC HPS HWY	HOUSTON LIGHTING AND POWER HOT MIXED ASPHALTIC CONCRETE HIGH-PRESSURE SODIUM HIGHWAY		
ID IE IP IR	INSIDE DIAMETER INVERT ELEVATION IRON PIPE IRON ROD		
JT JUNC	JOINT JUNCTION		
LF LN LPST LT	LINEAR FEET LANE LEAKING PETROLEUM STORAGE TANK LEFT		
MAX METRO MH MIN MON MRC	MAXIMUM METROPOLITAN TRANSIT AUTHORITY MANHOLE MINIMUM MONUMENT MONOLITHIC REINFORCED CONCRETE		
N NFV NO NTS	NORTH NOT FIELD VERIFIED NUMBER NOT TO SCALE		
OCEL OFS OLE OH	ON CURVE ELEVATION OFFSET OVERHEAD ELECTRICAL OVERHEAD		
PC PCC PCCP PERM PI PPCA PROP PT PT PVC	POINT OF CURVATURE POINT OF COMPOUND CURVATURE PRESTRESSED CONCRETE CYLINDER PIPE PERMANENT POINT OF INTERSECTION POTENTIALLY PETROLEUM CONTAMINATED AREA PROPOSED POINT POINT OF TANGENCY POINT OF VERTICAL CURVATURE, POLYVINYL CHLORIDE PIPE POINT OF VERTICAL INTERSECTION PAVEMENT POINT OF VERTICAL TANGENCY		
PVI PVM PVT			
Ⓡ R RCB RCP REINF REMOV ROW RD RRPM	RECORD DRAWING RADIUS OF CIRCULAR CURVE REINFORCED CONCRETE BOX REINFORCED CONCRETE PIPE REINFORCED REMOVABLE RIGHT OF WAY ROAD REFLECTIVE REMOVABLE PAVEMENT MARKERS		

ALL BEARINGS AND COORDINATES REFERENCED HEREON ARE GRID
VALUES BASED ON THE TEXAS COORDINATE SYSTEM OF 1983, SOUTH
CENTRAL ZONE NO. 4204 AND MAY BE CONVERTED TO SURFACE
VALUES BY MULTIPLYING BY THE FOLLOWING COMBINED SCALE
FACTOR OF 1.00010462

HARRIS COUNTY FLOODPLAIN REFERENCE MARKER 210215 IS A BRASS DISK STAMPED "W-140" IN THE SPRING BRANCH WATERSHED, STREAM NUMBER W140-00-00. BENCHMARK IS LOCATED 340' SOUTHWEST OF THE INTERSECTION OF WESTVIEW DR. AND PECO RD.
ELEVATION = 68.06' NAVD 1988, 2001 ADJ.


ALL SET PRIMARY CONTROL POINTS(1-6) MAY BE USED AS TEMPORARY BENCHMARKS.

CONTROL TABLE							
POINT No.	NORTHING	EASTING	ELEVATION	DESCRIPTION	STATION	OFFSET	ALIGNMENT
1	13850124.86	3083324.75	65.69	CP IRSC 58	10+14.19	2.28' RT	HICKORY SHADOWS
2	13849872.70	3083342.75	65.46	CP CHP	-0+34.91	5.06' RT	HICKORY SHADOWS
3	13849855.99	3082931.85	61.75	CP CHP	3+71.66	11.71' LT	HICKORY SHADOWS
4	13850104.15	3082918.16	62.33	CP CHP	6+11.44	12.03' LT	HICKORY SHADOWS
6	13850478.30	3082811.45	64.55	CP IRSC 58	5+09.99	6.30' RT	HICKORY SHADOWS WL



CERTIFICATION
I HEREBY CERTIFY THAT THE CONTROL POINTS
SHOWN HERE WERE DETERMINED BY A SURVEY MADE
ON THE GROUND ON 12/24/2024.

BRIAN D. SCOTT
REGISTERED PROFESSIONAL
LAND SURVEYOR
TEXAS REGISTRATION NO. 5280







COMBINED SCALE FACTOR NOTE:


ALL BEARINGS AND COORDINATES REFERENCED HEREON ARE GRID VALUES BASED ON THE TEXAS COORDINATE SYSTEM OF 1983, SOUTH CENTRAL ZONE NO. 4204 AND MAY BE CONVERTED TO SURFACE VALUES BY MULTIPLYING BY THE FOLLOWING COMBINED SCALE FACTOR OF 1.00010462

SITE BENCHMARK:

HARRIS COUNTY FLOODPLAIN REFERENCE MARKER 210215 IS A BRASS DISK STAMPED "W-140" IN THE SPRING BRANCH WATERSHED, STREAM NUMBER W140-00-00, BENCHMARK IS LOCATED 340' SOUTHWEST OF THE INTERSECTION OF WESTVIEW DR. AND PECH RD.
ELEVATION = 68.06' NAVD 1988, 2001 ADJ.




CERTIFICATION
I HEREBY CERTIFY THAT THE CONTROL POINTS
SHOWN HERE WERE DETERMINED BY A SURVEY MADE
ON THE GROUND ON 12/24/2024.



BRIAN D. SCOTT
REGISTERED PROFESSIONAL
LAND SURVEYOR
TEXAS REGISTRATION NO. 5280

MK.	DESCRIPTION		DATE	DWN.	CHK.				
<div style="text-align: center;">  <p>MBCO ENGINEERING + SURVEYING</p> <p>1200 Highway 6 South, Suite 180 Houston, Texas 77077 281.740.1866 MBCOEngineering.com SIC: NDC 086110 TPELS Engineering Firm No. F-36850 Land Surveying Firm No. 10194810</p> </div>									
<div style="text-align: center;">  <p>HDR</p> <p>HDR Engineering Inc. Texas Reg. No. 754 4828 Loop Central Drive, Suite 700 • Houston, Texas 77081 (713) 622-9264 • Fax (713) 622-9265 • www.hdrinc.com</p> </div>									
<div style="text-align: center;"> <p>City of Hilshire Village, Texas</p> <p>Hickory Shadows Drive Paving, Drainage & Utility Improvements</p> </div>									
<div style="text-align: center;"> <p>Hickory Shadows Survey Control Details</p> </div>									
Job No.: 10418041		Scale: HORZ : VERT : <div style="border: 1px solid black; padding: 2px; display: inline-block;">ONE INCH</div>				SHEET <div style="font-size: 2em; font-weight: bold; text-align: center;">04A</div>			
Date: JUNE, 2025		IF ABOVE HARK DOES NOT MEASURE ONE INCH, THEN THIS DWG. NOT TO SCALE				OF 28			
Dwn By: G.S. Fuller									
Chkd By: L. Le									



LEGEND

SHEET LIMITS AND SHEET NUMBER

WATER

PAVING & DRAINAGE

0 40' 80'

North arrow pointing up.

MK.	DESCRIPTION	DATE	DWN.	CHK.

FOR REVIEW ONLY

JUNE 2025

NGOC KIM LE

TX. LIC. 102192

NOT FOR BIDDING, OR CONSTRUCTION

HDR


HDR Engineering Inc. Texas Reg. No. 754
4828 Loop Central Drive, Suite 700 • Houston, Texas 77081
(713) 622-9264 • Fax (713) 622-9265 • www.hdrinc.com

City of Hilshire Village, Texas

**Hickory Shadows Drive
Paving, Drainage & Water Line Improvements**

OVERALL LAYOUT

Job No.: 10418041	Scale: HORIZ : 1" = 30'	SHEET 05 OF 28
Date: June, 2025	VERT : ONE INCH	
Dwn By: G.S. Fuller	IF ABOVE MARK DOES NOT MEASURE ONE INCH, THEN THIS DWG. NOT TO SCALE	
Chkd By: N. Le		



LEGEND

OVERALL DRAINAGE BOUNDARY



FLOW DIRECTION




DRAINAGE AREA DESIGNATION



CULVERT LABEL

DESIGNATION




CULVERT CAPACITY

FLOW (CFS)(2-YR)

NOTES:

1. DESIGN CRITERIA USED FOR STORM ANALYSIS IS THE LATEST HARRIS TX-DOT INTENSITY-DURATION FOR A 2-YEAR STORM EVENT WITH AN AVERAGE C VALUE OF 0.50.



Storm Sewer Hydrology & Hydraulic Calculations - 2 Year Storm Design
Hickory Shadows Drive Paving, Drainage, & Water Line Improvements
City of Hilshire Village

Job Section
Date: Tuesday, June 3, 2025
By: TC/NKL

Criteria:
HGL Starting Elevation for Drainage Basin = 59.20 (Top of Outfall Pipe)
Design Velocity = 3 NA 100 yr. Flood Elevation
Agency Curve Used = Harris-TxDOT
Year Storm Calculated = 2 2
Minimum pipe size proposed = 24 inches in diameter.
Pavement Thickness (Inches) = 7 in.
Subgrade Thickness (Inches) = 4 in.

Upstream Manhole / Inlet (From)	Downstream Manhole / Inlet (To)	Drainage Sub Area (Acres)	Total Area (Acres)	Runoff Coefficient 'C'	Sum of C*A	Time of Concentration 'TC'	Intensity based on 2 Year Storm	Bypass / Other Flow Added (cfs)	Sum of Flow (cfs)	Proposed Arch, Circular, or Box	Proposed Pipe	Prop. Top Wall Thickness (in)	Prop. Slope %	Prop. Design Capacity (cfs)	Pipe Length (Feet)	Pipe Fall (ft)	Manhole Drop / Pipe Drop (ft)	Flow line Elevation Upstream (ft)	Flow line Elevation Downstream (ft)	Actual Velocity (fps)	Travel Time (min)	Hydraulic Gradient % based on 2 Year Storm	Change in Head (ft) based on 2 Year Storm	2 Year Storm Upstream Hydraulic Elev.	2 Year Storm Downstream Hydraulic Elev.
Storm sewer along Hickory Shadows Drive																									
Inlet Laterals																									
A1	M1	0.935	0.935	0.50	0.468	24.88	3.66	0.00	1.71	C	24"	3.00	0.45%	15.25	22	0.10	0.00	57.76	57.66	0.54	0.67	0.006%	0.001	59.28	59.27
A2	M1	1.630	1.630	0.50	0.815	25.90	3.58	0.00	2.92	C	24"	3.00	1.66%	29.14	6	0.10	0.00	57.76	57.66	0.93	0.11	0.017%	0.001	59.28	59.27
A3	M2	1.281	1.281	0.50	0.641	25.45	3.62	0.00	2.32	C	24"	3.00	0.77%	19.85	24	0.18	0.00	57.53	57.35	0.74	0.54	0.011%	0.003	59.22	59.21
A4	OUTFALL	1.677	1.677	0.50	0.839	25.95	3.58	0.00	3.00	C	24"	3.00	0.00%	0.00	0	0.00	0.00	57.20	57.20	0.96	0.00	0.018%	0.000	59.21	59.21
Trunk Line																									
M1	M2	2.565	2.565	0.50	1.283	26.40	3.52	0.00	4.51	C	24"	3.00	0.20%	10.11	153	0.31	0.00	57.66	57.35	1.44	1.78	0.040%	0.061	59.27	59.21
M2	A4/OUTFALL	1.281	5.523	0.50	2.762	28.51	3.62	0.00	9.99	C	24"	3.00	2.14%	33.09	7	0.15	0.00	57.35	57.20	3.18	0.04	0.195%	0.014	59.21	59.20

MK.	DESCRIPTION	DATE	DWN.	CHK.

FOR REVIEW ONLY
JUNE 2025
NGOC KIM LE
TX. LIC. 102192
NOT FOR BIDDING
OR
CONSTRUCTION

HDR
HDR Engineering Inc. Texas Reg. No. 754
4828 Loop Central Drive, Suite 700 • Houston, Texas 77081
(713) 622-9264 • Fax (713) 622-9265 • www.hdrinc.com

City of Hilshire Village, Texas
Hickory Shadows Drive
Paving, Drainage & Water Line Improvements

Drainage Area Map

Job No.: 10418041	Scale: HORZ : 1" = 40'	SHEET 06 OF 28
Date: June, 2025	VERT : 1" = 4'	
Dwn By: G.S. Fuller	ONE INCH	
Chkd By: N. Le	IF ABOVE MARK DOES NOT MEASURE ONE INCH, THEN THIS DWG. NOT TO SCALE	

GENERAL TRAFFIC CONTROL NOTES:

1. IF THE CONTRACTOR CHOOSES TO USE A DIFFERENT METHOD OF "TRAFFIC CONTROL PLAN" DURING CONSTRUCTION THAN WHAT IS OUTLINED IN CONTRACT DRAWINGS HE/SHE SHALL BE RESPONSIBLE TO PREPARE AND SUBMIT AN ALTERNATIVE SET OF PLANS TO PLAN REVIEW FOR APPROVAL THREE WEEKS PRIOR TO BEGINNING CONSTRUCTION. THESE PLANS SHALL BE DRAWN TO SCALE AND SEALED BY A P.E. IN THE STATE OF TEXAS.
2. THE CONTRACTOR SHALL PROVIDE AND INSTALL TRAFFIC CONTROL DEVICES IN CONFORMANCE WITH PART VI OF TEXAS MANUAL ON UNIFORM TRAFFIC CONTROL DEVICES (TXMUTCD - LATEST EDITION WITH REVISIONS) DURING CONSTRUCTION. FOR A 30 MPH ROADWAY, SIGNS SHALL BE PLACED MIN. 120' APART PER MINIMUM SIGN SPACING DISTANCE 'X' FROM "TRAFFIC CONTROL PLAN ONE-LANE TWO-WAY TRAFFIC CONTROL" DETAIL.
3. CONTRACTOR SHALL NOTIFY CITY 72 HOURS PRIOR TO INSTALLING TRAFFIC CONTROL DEVICES.
4. THE TCP PLAN SHALL BE COORDINATED WITH ALL LOCAL AGENCIES AND SERVICES THAT MAY BE IMPACTED BY THE CONSTRUCTION, INCLUDING BUT NOT LIMITED TO EMERGENCY RESPONSE AGENCIES SUCH AS CITY POLICE DEPARTMENT, FIRE DEPARTMENT, TRASH PICKUP, USPS, SCHOOLS, AND TXDOT.
5. NO WORK WILL BE ALLOWED ON SATURDAYS OR HOLIDAYS, WITHOUT PRIOR AUTHORIZATION BY CITY STAFF.
6. THE CONTRACTOR SHALL NOT STORE ANY CONSTRUCTION MATERIALS IN SUCH A MANNER AS TO OBSTRUCT VEHICLE DRIVER SIGHT DISTANCES.
7. ALL SIGNS, WARNING DEVICES, AND BARRICADES ARE THE SOLE RESPONSIBILITY OF THE CONTRACTOR, INCLUDING ACTS OF VANDALISM OR ACCIDENT. THE CONTRACTOR SHALL INSURE THAT ALL BARRICADES, SIGNS, CHANNELIZING DEVICES, WARNING LIGHTS, TRAFFIC HANDLING DEVICES, AND TEMPORARY AND EXISTING PAVEMENT MARKINGS ARE MAINTAINED IN A CLEAN FUNCTIONAL CONDITION AT ALL TIMES.
8. THE CONTRACTOR SHALL REMOVE ALL EXISTING SIGNS WHICH ARE IN CONFLICT WITH THE CONSTRUCTION SIGNS.
9. NOTHING IN THESE NOTES OR PLANS SHALL RELIEVE THE CONTRACTOR OF THE RESPONSIBILITY FOR JOB SITE CONDITIONS DURING THE COURSE OF CONSTRUCTION OF THE PROJECT; INCLUDING SAFETY OF ALL MODES OF TRANSPORTATION, PERSONS, AND PROPERTY, AND THAT THIS REQUIREMENT SHALL APPLY CONTINUOUSLY AND NOT BE LIMITED TO WORKING HOURS. PROJECT SITE AND PROPOSED IMPROVEMENTS TO BE MAINTAINED AND CONTRACTOR TO CLEAN UP AT THE END OF EACH DAY AS APPROVED BY THE ENGINEER AND CITY.
10. THE CITY HAS THE RIGHT TO DEMAND THE INSTALLATION OF ADDITIONAL TRAFFIC CONTROL DEVICES OR MODIFICATIONS OF THESE PLANS AND NOTES, AS DEEMED NECESSARY TO PROMOTE THE SAFE AND ORDERLY FLOW OF TRAFFIC, INCLUDING PEDESTRIANS AND BICYCLES, THROUGH THE CONSTRUCTION WORK ZONE. THE CONTRACTOR SHALL COMPLY WITH THESE ADDITIONAL REQUESTS OR MODIFICATIONS WITH DUE DILIGENCE.
11. WHEN ENTERING OR LEAVING ROADWAYS CARRYING PUBLIC TRAFFIC, THE CONTRACTOR'S EQUIPMENT WHETHER EMPTY OR LOADED SHALL IN ALL CASES YIELD TO PUBLIC TRAFFIC WITH ASSISTANCE OF CONTRACTOR PROVIDED CERTIFIED FLAGGER/OFF-DUTY OFFICER.
12. ACCESS TO DRIVEWAYS ADJACENT TO THE CONSTRUCTION WORK ZONE SHALL BE MAINTAINED AT ALL TIMES. ADDITIONAL CONES AND DELINEATORS MAY BE REQUIRED TO DELINEATE THE DRIVEWAY ACCESS ROUTE THROUGH THE CONSTRUCTION ZONE. A MINIMUM OF A 10' TRAVEL LANE SHALL BE MAINTAINED AT ALL TIMES.
13. CONTRACTOR SHALL PROVIDE A TEMPORARY DRIVEWAY FOR RESIDENTS UNTIL THE DRIVEWAY HAS BEEN REPLACED. THIS SHALL BE INCIDENTAL TO THE TRAFFIC CONTROL PAY ITEM.
14. CONTRACTOR SHALL BE RESPONSIBLE FOR NOTIFYING THE RESIDENTS A MINIMUM OF 7 DAYS PRIOR TO WORKING IN FRONT OF THEIR PROPERTY.
15. SPILLAGE RESULTING FROM HAULING OPERATIONS ALONG OR ACROSS ANY PUBLIC TRAVELED WAY SHALL BE REMOVED IMMEDIATELY BY THE CONTRACTOR.
16. THE CONTRACTOR SHALL MAINTAIN POSITIVE DRAINAGE THROUGHOUT THE PROJECT AT ALL TIMES.
17. THE CONTRACTOR SHALL COORDINATE HIS SCHEDULE OF WORK WITH UTILITY OWNERS, BOTH PUBLIC AND PRIVATE. UTILITY OWNERS MAY HAVE THERE OWN FORCES OR CONTRACTORS RELOCATING FACILITIES REQUIRED BY THE NEW CONSTRUCTION, THE CONTRACTOR SHALL COORDINATE AND COOPERATE WITH THESE OTHER FORCES OR CONTRACTORS.
18. FLASHING WARNING LIGHTS AND/OR FLAGS MAY BE USED TO CALL ATTENTION TO THE ADVANCE WARNING SIGNS.
19. ALL WORK SHALL BE PURSUED IN ACCORDANCE WITH CITY ORDINANCE NO. 40-28. NO WORK SHALL BE DONE ON HICKORY SHADOWS DRIVE IN THE ROADWAY BETWEEN HOURS OF 7:00 AM TO 9:00 AM AND 4:00 PM TO 6:00 PM, MONDAY-FRIDAY. ALL OTHER ROADWAYS SHALL HAVE WORKING HOURS OF 7:00 AM TO 6:00 PM.
20. CONTRACTOR SHALL COVER OPEN EXCAVATIONS DURING NON-WORKING HOURS. ANCHORED STEEL PLATES SHALL BE USED TO COVER EXCAVATION WITHIN THE PAVEMENT, EXCAVATIONS OUTSIDE OF PAVEMENT SHALL BE COVERED AND ENCLOSED IN CONSTRUCTION FENCING AND OPEN THE LANES FOR TRAFFIC.

MK.	DESCRIPTION	DATE	DWN.	CHK.
<div>FOR REVIEW ONLY JUNE 2025 NGOC KIM LE TX. LIC. 102192 NOT FOR BIDDING OR CONSTRUCTION</div>				
<div><div>HDR</div><div>HDR Engineering Inc. Texas Reg. No. 754 4828 Loop Central Drive, Suite 700 • Houston, Texas 77081 (713) 622-9264 • Fax (713) 622-9265 • www.hdrinc.com</div></div>				
City of Hilshire Village, Texas				
Hickory Shadows Drive Paving, Drainage & Water Line Improvements				
TRAFFIC CONTROL PLAN GENERAL NOTES				
Job No.: 10418041	Scale: HORIZ : VERT : ONE INCH	SHEET 07		
Date: June, 2025				
Dwn By: G.S. Fuller				
Chkd By: N. Le				
		IF ABOVE MARK DOES NOT MEASURE ONE INCH, THEN THIS DWG. NOT TO SCALE		OF 28

MK.	DESCRIPTION	DATE	DWN.	CHK.
<div style="text-align: center;">FOR REVIEW ONLY</div> <div style="margin-top: -8px; font-size: small;"><div>JUNE 2025</div><div>NGOC KIM LE</div><div>Tx. LIC. 102192</div><div>NOT FOR BIDDING OR CONSTRUCTION</div></div>				

HDR


HDR Engineering Inc., Texas Reg. No. 754
 4828 Loop Central Drive, Suite 700 • Houston, Texas 77081
 (713) 622-9264 • Fax (713) 622-9265 • www.hdrinc.com

City of Hillshire Village, Texas


Hickory Shadows Drive Paving, Drainage & Water Line Improvements

Traffic Control Map Phase 1 & 2


Job No.: I04I804I	Scale: <div>HORIZ : 1" = 30'</div> VERT :	SHEET
Date: June, 2025	<div>[ONE INCH]</div> <div style="font-size: x-small;">IF ABOVE MARK DOES NOT MEASURE ONE INCH THEN THIS DWG. NOT TO SCALE</div>	08
Dwn By: G.S. Fuller		
Chkd By: N. Le		OF 28



- PHASE 3 NOTES:**
1. PLACE EROSION CONTROL ITEMS WHERE APPLICABLE (TYPICAL OF ALL TRAFFIC CONTROL PLAN NARRATIVE SEQUENCE ITEMS.)
 2. PLACE TRAFFIC CONTROL SIGNS AND DEVICES FOR PHASE 3 IN ACCORDANCE WITH TYPICAL SECTIONS AND CONSTRUCTION SEQUENCE LAYOUT.
 3. CONTRACTOR SHALL CONSTRUCT PAVEMENT IN APPLICABLE SECTIONS (PHASE 3A, 3B AND 3C). CONSTRUCT WALKWAYS AND DRIVEWAYS ON APPLICABLE SIDE OF HICKORY SHADOWS DRIVE.
 4. CONTRACTOR SHALL SEQUENCE CONSTRUCTION IN SUCH A MANNER THAT DRIVEWAYS ACCESS IS MAINTAINED AS MUCH AS POSSIBLE. CONTRACTOR TO VERIFY WITH ALL RESIDENTS IF ANY SPECIAL DRIVEWAY ACCESS IS NEEDED.
 5. THE RESIDENTS AT 1 HICKORY SHADOWS REQUIRE CONTINUOUS ACCESS TO THEIR DRIVEWAY AND HOME. CONTRACTOR SHALL PROVIDE CONSTANT ACCESS TO DRIVEWAY THROUGHOUT THE ENTIRETY OF PROJECT DURATION AS NOTED IN PLANS.
 6. CONTRACTOR SHALL PROVIDE 72 HOUR NOTICE TO RESIDENTS PRIOR TO DRIVEWAY REMOVAL OR UTILITY SERVICE DISRUPTION.



GENERAL TYPICAL SECTION FOR PAVING HALF OF THE ROAD



- LEGEND**
- PHASE 3A CONSTRUCTION
 - PHASE 3B CONSTRUCTION
 - PHASE 3C CONSTRUCTION
 - BARRELS OR DRUMS
 - GROUND MOUNTED SIGN
 - TYPE III BARRICADE
 - PROP DIRECTION OF TRAFFIC
 - EXIST DIRECTION OF TRAFFIC
- TRAFFIC CONTROL SIGNS:**
- A: ONE LANE ROAD (CW20-4)
 - B: ROAD CLOSED (R11-2, 48"x30")
 - C: DO NOT ENTER (R5-1, 30"x30")
 - D: NO RIGHT TURN (R3-1, 24"x24")
 - E: DETOUR AHEAD (CW20-2, 36"x36")
 - F: DETOUR (M4-9N, 30"x12")
 - G: DETOUR (M4-9R, 30"x24")
 - H: ROAD WORK AHEAD (CW20-1, 36"x36")

- NOTES:**
1. UTILIZE FLAGMEN AS NECESSARY AND INSTALL STORM WATER POLLUTION PREVENTION AND TREE PROTECTION ITEMS.
 2. CONTRACTOR SHALL COORDINATE WITH THE POLICE & FIRE DEPARTMENT DURING THE CONSTRUCTION PHASE FOR ROAD CLOSURE AND EMERGENCY ACCESS.

PHASE 3 CONSTRUCTION SEQUENCE

MK.	DESCRIPTION	DATE	DWN.	CHK.

FOR REVIEW ONLY

JUNE 2025

NGOC KIM LE

TX. LIC. 102192

NOT FOR BIDDING OR CONSTRUCTION

HDR



HDR Engineering Inc. Texas Reg. No. 754
4828 Loop Central Drive, Suite 700 • Houston, Texas 77081
(713) 622-9264 • Fax (713) 622-9265 • www.hdrinc.com











City of Hilshire Village, Texas

Hickory Shadows Drive
Paving, Drainage & Water Line Improvements

Traffic Control Map Phase 3

Job No.: 10418041	Scale: HORZ : 1" = 30'	SHEET 09 OF 28
Date: June, 2025	VERT : 1" = 30'	
Dwn By: G.S. Fuller	ONE INCH	
Chkd By: N. Le	IF ABOVE MARK DOES NOT MEASURE ONE INCH, THEN THIS DWG. NOT TO SCALE	

DATE:
FILE:

LEGEND			
	Type 3 Barricade		Channelizing Devices
	Heavy Work Vehicle		Truck Mounted Attenuator (TMA)
	Trailer Mounted Flashing Arrow Board		Portable Changeable Message Sign (PCMS)
	Sign		Traffic Flow
	Flag		Flagger

Posted Speed *	Formula	Minimum Desirable Taper Lengths **			Suggested Maximum Spacing of Channelizing Devices		Minimum Sign Spacing "A" Distance	Suggested Longitudinal Buffer Space "B"	Stopping Sight Distance
		10' Offset	11' Offset	12' Offset	On a Taper	On a Tangent			
30	L = WS ² / ₆₀	150'	165'	180'	30'	60'	120'	90'	200'
35		205'	225'	245'	35'	70'	160'	120'	250'
40		265'	295'	320'	40'	80'	240'	155'	305'
45		450'	495'	540'	45'	90'	320'	195'	360'
50	L = WS	500'	550'	600'	50'	100'	400'	240'	425'
55		550'	605'	660'	55'	110'	500'	295'	495'
60		600'	660'	720'	60'	120'	600'	350'	570'
65		650'	715'	780'	65'	130'	700'	410'	645'
70		700'	770'	840'	70'	140'	800'	475'	730'
75		750'	825'	900'	75'	150'	900'	540'	820'

* Conventional Roads Only

** Taper lengths have been rounded off.

L=Length of Taper (FT) W=Width of Offset (FT) S=Posted Speed (MPH)

TYPICAL USAGE				
MOBILE	SHORT DURATION	SHORT TERM STATIONARY	INTERMEDIATE TERM STATIONARY	LONG TERM STATIONARY
	✓	✓		

GENERAL NOTES


1. Flags attached to signs where shown are REQUIRED.
2. All traffic control devices illustrated are REQUIRED, except those denoted with the triangle symbol may be omitted when stated elsewhere in the plans, or for routine maintenance work, when approved by the Engineer.
3. The CW3-4 "BE PREPARED TO STOP" sign may be installed after the CW20-4D "ONE LANE ROAD AHEAD" sign, but proper sign spacing shall be maintained.
4. Sign spacing may be increased or an additional CW20-1D "ROAD WORK AHEAD" sign may be used if advance warning ahead of the flagger or RI-2 "YIELD" sign is less than 1500 feet.
5. A Shadow Vehicle with a TMA should be used anytime it can be positioned 30 to 100 feet in advance of the area of crew exposure without adversely affecting the performance or quality of the work. If workers are no longer present but road or work conditions require the traffic control to remain in place, Type 3 Barricades or other channelizing devices may be substituted for the Shadow Vehicle and TMA.
6. Additional Shadow Vehicles with TMAs may be positioned off the paved surface, next to those shown in order to protect wider work spaces.


TCP (1-2a)

7. R1-2 "YIELD" sign traffic control may be used on projects with approaches that have adequate sight distance. For projects in urban areas, work spaces should be no longer than one half city block. In rural areas on roadways with less than 2000 ADT, work spaces should be no longer than 400 feet.
8. R1-2 "YIELD" sign with R1-20P "TO ONCOMING TRAFFIC" plaque shall be placed on a support at a 7 foot minimum mounting height.

TCP (1-2b)


9. Flaggers should use two-way radios or other methods of communication to control traffic.
10. Length of work space should be based on the ability of flaggers to communicate.
11. If the work space is located near a horizontal or vertical curve, the buffer distances should be increased in order to maintain adequate stopping sight distance to the flagger and a queue of stopped vehicles (see table above).
12. Channelizing devices on the center-line may be omitted when a pilot car is leading traffic and approved by the supervisor.
13. Flaggers should use 24" STOP/SLOW paddles to control traffic. Flags should be limited to emergency situations.

 <p>Texas Department of Transportation</p>	<p><i>Operations Division Standard</i></p>																				
<h1 style="margin: 0;">TRAFFIC CONTROL PLAN</h1> <h2 style="margin: 0;">ONE-LANE TWO-WAY</h2> <h2 style="margin: 0;">TRAFFIC CONTROL</h2> <h3 style="margin: 20px 0 0 0;">TCP (1-2) - 18</h3>																					
<table border="1" style="width: 100%; border-collapse: collapse;"> <tr> <td style="width: 40%;">FILE# tcpl-2-18.dgn</td> <td style="width: 10%;">DNI</td> <td style="width: 10%;">CK1</td> <td style="width: 10%;">DWI</td> <td style="width: 10%;">CK1</td> </tr> <tr> <td>© TxDOT December 1985</td> <td>CONT</td> <td>SECT</td> <td>JOB</td> <td>HIGHWAY</td> </tr> <tr> <td>4-90 4-98 2-94 2-12 1-97 2-18</td> <td colspan="2">REVISONS</td> <td colspan="2"></td> </tr> <tr> <td></td> <td>DIST</td> <td colspan="2">COUNTY</td> <td>SHEET NO</td> </tr> </table>		FILE# tcpl-2-18.dgn	DNI	CK1	DWI	CK1	© TxDOT December 1985	CONT	SECT	JOB	HIGHWAY	4-90 4-98 2-94 2-12 1-97 2-18	REVISONS					DIST	COUNTY		SHEET NO
FILE# tcpl-2-18.dgn	DNI	CK1	DWI	CK1																	
© TxDOT December 1985	CONT	SECT	JOB	HIGHWAY																	
4-90 4-98 2-94 2-12 1-97 2-18	REVISONS																				
	DIST	COUNTY		SHEET NO																	




TYPE III BARRICADE FOR END OF ROAD

FOR TYPE III BARRICADE FOR END OF ROAD, THE THREE (3) RAILS SHALL BE REFLECTIVE RED AND REFLECTIVE WHITE STRIPES ON SIDE FACING TRAFFIC




DEMOUNTABLE TYPE III BARRICADE



DRUMS

DRUMS, SET ON END, AND USED FOR TRAFFIC WARNING OR CHANNELIZATION SHALL BE APPROX 36" IN HEIGHT AND A MIN OF 18" IN DIAMETER. THE CONTRACTOR, AT HIS OPTION, MAY USE DRUMS MADE FROM STEEL BARRELS OR BLACK POLYETHYLENE PLASTIC DRUM LINERS WEIGHING APPROX EIGHT POUNDS EACH. THE MARKINGS ON DRUMS SHALL BE HORIZONTAL, CIRCUMFERENTIAL, REFLECTORIZED ORANGE AND REFLECTORIZED WHITE STRIPES, 4 TO 8 INCHES WIDE. THE FIRST REFLECTORIZED STRIPE SHOULD START WITHIN TWO (2) INCHES OF THE TOP OF THE DRUM. THERE SHALL BE AT LEAST TWO ORANGE AND TWO WHITE STRIPES ON EACH DRUM. IF THERE ARE NON- REFLECTORIZED SPACES BETWEEN THE HORIZONTAL ORANGE AND WHITE STRIPES, THEY SHALL BE NO MORE THAN 2 INCHES WIDE. METAL DRUMS SHALL BE PAINTED BLACK OR ORANGE BEFORE REFLECTORIZED STRIPES ARE ADDED. ALL DRUMS ON PROJECT WILL BE THE SAME COLOR. WHEN DRUMS ARE PLACED IN THE ROADWAY, APPROPRIATE WARNING SIGNS SHOULD BE USED. DURING HOURS OF DARKNESS, A FLASHING WARNING LIGHT SHOULD BE PLACED ON DRUMS USED SINGLY AS A WARNING DEVICE. STEADY BURN ELECTRIC LIGHTS OR DELINEATORS SHOULD BE PLACED ON DRUMS USED IN SERIES FOR TRAFFIC CHANNELIZATION. DRUMS SHALL BE WEIGHTED WITH SAND TO THE EXTENT INDICATED IN THE PLANS.

CWI-8 CHEVRON SIGNS, CWI-6A ARROW SIGNS OR VP-I VERTICAL PANELS MOUNTED ABOVE DRUMS MAY BE USED AS SUPPLEMENTS TO DRUM DELINEATION.




CONES

TRAFFIC CONES AND TUBULAR MARKERS SHALL BE A MIN OF 18" INCHES IN HEIGHT WITH A BROADENED BASE AND MAY BE MADE OF VARIOUS MATERIALS TO WITHSTAND IMPACT WITHOUT DAMAGE TO THEMSELVES OR TO VEHICLES. LARGER SIZES SHOULD BE USED ON FREEWAYS AND OTHER ROADWAYS WHERE SPEED ARE RELATIVELY HIGH OR WHERE EVER MORE CONSPICUOUS GUIDANCE IS NEEDED. ORANGE SHALL BE THE PREDOMINANT COLOR ON CONES AND TUBULAR MARKERS. THEY SHOULD BE KEPT CLEAN AND BRIGHT FOR MAX TARGET VALUE. FOR NIGHTTIME USE THEY SHALL BE REFLECTORIZED OR EQUIPPED WITH LIGHTING DEVICES FOR MAX VISIBILITY. REFLECTORIZED MATERIAL SHALL HAVE A SMOOTH, SEALED OUTER SURFACE WHICH WILL DISPLAY THE SAME APPROX COLOR DAY AND NIGHT.


REFLECTORIZATION OF TUBULAR MARKERS SHALL BE A MIN OF TWO THREE-INCH BANDS PLACED A MAX OF 2" FROM THE TOP WITH A MAX OF 6" BETWEEN THE BANDS. REFLECTORIZATION OF CONES SHALL BE PROVIDED BY A MIN 6" BAND PLACED A MAX OF 3" FROM THE TOP.

CONES OR TUBULAR MARKERS ARE GENERALLY ONLY SUITABLE FOR TEMPORARY USAGE (UP TO 8 HOURS) WITH OTHER CHANNELIZATION DEVICES SUCH AS VERTICAL PANELS OR BARRICADES PREFERRED FOR LONGER TERM USAGE. CARE SHOULD BE TAKEN TO INSURE THAT THEY REMAIN IN THEIR PROPER LOCATION AND IN AN UPRIGHT POSITION.



VERTICAL PANELS (VP)


VERTICAL PANELS ARE NORMALLY USED AS CHANNELIZING DEVICES TO INDICATE TANGENT OR NEARLY TANGENT ROADWAY ALIGNMENT WHERE GOOD TARGET VALUE OF A DEVICE IS NEEDED IN DAYTIME AS WELL AS THE NIGHTTIME. IN ADDITION, VERTICAL PANELS SHOULD BE USED AT THE EDGE OF SHOULDER DROP-OFFS AND OTHER SUCH AREAS AS LANE TRANSITIONS WHERE POSITIVE DAY AND NIGHT DELINEATION MAY BE REQUIRED. VERTICAL PANELS SHOULD BE MOUNTED BACK TO BACK IF USED AT THE EDGE OF CUTS ADJACENT TO TWO-WAY TWO LANE ROADWAYS. STRIPES SHOULD ALWAYS SLOPE DOWNWARD TOWARD THE TRAVELED WAY.




PORTABLE RIGID VERTICAL PANEL

SEE COMPLIANT PRODUCTS LIST FOR ALTERNATE DESIGNS.


- CHANNELIZING DEVICES ON SELF-RIGHTING SUPPORTS MAY BE A VERTICAL PANEL, OPPOSING LANE DIVIDER OR CHEVRON.
- CHANNELIZING DEVICES ON SELF-RIGHTING SUPPORTS SHALL BE USED AT LOCATIONS DETAILED ELSEWHERE IN THE PLANS. THESE DEVICES SHALL CONFORM TO THE "TEXAS MANUAL ON UNIFORM TRAFFIC CONTROL DEVICES".
- THE CONTRACTOR SHALL MAINTAIN DEVICES IN A CLEAN CONDITION AND REPLACED DAMAGED, NON-REFLECTIVE, FADED, OR BROKEN DEVICES AND BASES AS NECESSARY.
- PORTABLE BASES SHALL BE FABRICATED FROM VIRGIN AND/OR RECYCLED RUBBER. APPROXIMATE WEIGHT OF PORTABLE BASES SHALL BE 35 LBS.




"A" FRAME




DEMOUNTABLE



TYPE I




TYPE II



FIXED BASE W/ APPROVED ADHESIVE (DRIVEABLE BASE, OR FLEXIBLE SUPPORT CAN BE USED)

CHEVRONS

- THE CHEVRON SHALL BE A VERTICAL RECTANGLE WITH A MINIMUM SIZE OF 12 BY 18 INCHES.
- CHEVRONS ARE INTENDED TO GIVE NOTICE OF A SHARP CHANGE OF ALIGNMENT WITH THE DIRECTION OF TRAVEL AND PROVIDE ADDITIONAL EMPHASIS AND GUIDANCE FOR VEHICLE OPERATORS WITH REGARD TO CHANGES IN HORIZONTAL ALIGNMENT OF THE ROADWAY.
- CHEVRONS, WHEN USED, SHALL BE ERECTED ON THE OUTSIDE OF A SHARP CURVE OR TURN, OR ON THE FAR SIDE OF AN INTERSECTION. THEY SHALL BE IN LINE WITH AND AT RIGHT ANGLES TO APPROACHING TRAFFIC. SPACING SHOULD BE SUCH THAT THE MOTORIST ALWAYS HAS THREE IN VIEW, UNTIL THE CHANGE IN ALIGNMENT ELIMINATES ITS NEEDED.
- TO BE EFFECTIVE, THE CHEVRON SHOULD BE VISIBLE FOR AT LEAST 500 FEET.
- CHEVRONS SHALL BE ORANGE WITH A BLACK NON-REFLECTIVE LEGEND. SHEETING FOR THE CHEVRON SHALL BE RETROREFLECTIVE TYPE E (FLUORESCENT PRISMATIC) CONFORMING TO DEPARTMENTAL MATERIAL SPECIFICATION DMS-8300, UNLESS NOTED OTHERWISE. THE LEGEND SHALL BE BLACK VINYL NON-REFLECTIVE DECAL SHEETING MEETING THE REQUIREMENTS OF DMS-8320.



STRIPING FOR BARRICADE

BARRICADE NOTES

THE MOST RECENT EDITION OF THE TEXAS MANUAL ON UNIFORM TRAFFIC CONTROL DEVICES, AND IT'S REVISIONS, SHALL GOVERN THE CONSTRUCTION AND USE OF ALL ITEMS HEREIN DESCRIBED.

CHANNELIZATION DEVICES OTHER THAN BARRICADES SHOULD NORMALLY BE USED FOR CHANNELIZATION PURPOSES.

BARRICADES SHOULD NORMALLY BE PLACED PERPENDICULAR TO THE TRAFFIC FLOW. OTHER CHANNELIZING DEVICES, SUCH AS DRUMS, VERTICAL PANELS OR PORTABLE BARRIERS, SHOULD BE USED WHERE NEEDED TO SEPARATE TRAFFIC FROM THE WORK AREA. IN ALL CASES, THE BARRICADES SHOULD BE SO LOCATED AS TO MOST ADVANTAGEOUSLY WARN AND DIRECT TRAFFIC.


BARRICADES MAY BE DESIGNED AND CONSTRUCTED FROM WOOD OR ANY OTHER SUITABLE MATERIAL IN A MANNER APPROVED BY THE DEPARTMENT OF TRAFFIC AND TRANSPORTATION. THE CONSTRUCTION DETAILS SHOWN HEREON ARE TYPICAL AND ARE SUGGESTED DETAILS FOR WOOD SUPPORT SYSTEMS FOR BARRICADES. THE DETAILS OF RAIL WIDTH AND STRIPING, NUMBER AND SPACING OF RAILS, MINIMUM LENGTH AND HEIGHT (ABOVE PAVEMENT) OF RAILS MUST BE ADHERED TO WHEN ALTERNATE DESIGNS ARE USED.

BARRICADES ARE TO BE CONSTRUCTED OF CLEAN SOUND MATERIAL. ALL SURFACES ABOVE GROUND, WHICH ARE NOT STRIPED, SHALL BE WHITE EXCEPT THE UNPAINTED GALVANIZED METAL OR ALUMINUM COMPONENTS MAY BE USED. COMPONENTS MADE OF LUMBER SHALL BE PAINTED WITH A MINIMUM OF TWO COATS OF AN APPROVED BRAND OF WHITE PAINT TO SECURE THOROUGH COVERAGE AND A UNIFORM WHITE COLOR.


THE REFLECTORIZED WHITE AND REFLECTORIZED ORANGE (REFLECTORIZED RED) STRIPES FOR BARRICADES, DRUMS AND VERTICAL PANELS SHALL BE CONSTRUCTED OF "HIGH INTENSITY" SHEETING AND SHALL BE MAINTAINED TO MEET THE APPEARANCE, COLOR AND REFLECTIVITY REQUIREMENTS SET BY DOT.

THE CONTRACTOR SHALL MAINTAIN EACH BARRICADE IN A CLEAN AND GOOD CONDITION.


BARRICADES SHALL BE REMOVED UPON COMPLETION OF THE WORK AND/OR THE ELIMINATION OF THE HAZARD ON ANY SECTION.




STAND FOR TYPE III BARRICADE



TYPE II



GATE FOR TYPE III BARRICADE



POST FOR TYPE III BARRICADE

MK.	DESCRIPTION	DATE	DWN.	CHK.



HDR Engineering Inc. Texas Reg. No. 754
4828 Loop Central Drive, Suite 700 • Houston, Texas 77081
(713) 622-9264 • Fax (713) 622-9265 • www.hdrinc.com

City of Hilshire Village, Texas

Hickory Shadows Drive
Paving, Drainage & Water Line Improvements



TYPICAL TRAFFIC CONTROL DETAILS

Job No.: 10418041
Date: June, 2025
Dwn By: G.S. Fuller
Chld By: N. Le

Scale:
HORZ :
VERT :
ONE INCH
IF ABOVE MARK DOES NOT
MEASURE ONE INCH, THEN
THIS DWG. NOT TO SCALE


SHEET
11
OF 28

CONTRACTOR SHALL UTILIZE ZERO CURB CUTBACK THROUGHOUT THE STREET RECONSTRUCTION AREA.



IMPROVEMENTS LEGEND:
UTILITIES, PAVING & DRAINAGE:

- Proposed 1 1/2\" Short Side Water Service Replacement with New Meter Box.
- Proposed 1 1/2\" Long Side Water Service Replacement with New Meter Box.
- Remove and Salvage Existing Fire Hydrants.
- Abandon Existing Water Valve as Per Specifications.
- Abandon Existing Water Line Per Specifications.
- Proposed Concrete pavement. (See Typical Single Roadway Section on Sheet 21)
- Remove and Dispose of Existing Concrete Pavement and Base Course with Curb.
- Remove and Reset Mailboxes. (Contractor to Verify if Removal is Required)
- Proposed Walkway Replacement. (See Sidewalk Details on Sheet 22)
- Proposed Pavement Header. (See Type I Paving Header Detail on Sheet 21)
- Remove Existing Storm Sewer Inlet.
- Remove Existing Storm Sewer.
- Contractor Shall Coordinate Support, Adjustment or Relocation of Power/Light Poles and/or Guy Anchors w/Owner of Poles, as Required.
- Remove and Replace Driveway with Concrete. (See Driveway Details on Sheet 22)
- Remove and Relocate Sign.
- Cut and Plug Sprinkler Head at R.O.W - No Replacement.
- Remove and Replace existing Yard Drain using 4\" PVC Pipe to penetrate through Proposed Curb. (No Separate Payment)



MK.	DESCRIPTION	DATE	DWN.	CHK.

FOR REVIEW ONLY

JUNE 2025

NGOC KIM LE
TX. LIC. 102192
NOT FOR BIDDING
OR
CONSTRUCTION

HDR

HDR Engineering Inc. Texas Reg. No. 754
4828 Loop Central Drive, Suite 700 • Houston, Texas 77081
(713) 622-9264 • Fax (713) 622-9265 • www.hdrinc.com



City of Hilshire Village, Texas

Hickory Shadows Drive
Paving, Drainage & Water Line Improvements

HICKORY SHADOWS
STA. -1+00.00 TO STA. 2+75.00

Job No.: 10418041	Scale: HORIZ : 1" = 20' VERT : 1" = 2'	<p>12</p> <p>OF 28</p>
Date: June, 2025	ONE INCH	
Dwn By: G.S. Fuller	IF ABOVE MARK DOES NOT MEASURE ONE INCH, THEN THIS DWG. NOT TO SCALE	
Chkd By: N. Le		

CONTRACTOR SHALL UTILIZE ZERO CURB CUTBACK THROUGHOUT THE STREET RECONSTRUCTION AREA.



IMPROVEMENTS LEGEND:
UTILITIES, PAVING & DRAINAGE:


- Proposed 1 1/2" Short Side Water Service Replacement with New Meter Box.
- Proposed 1 1/2" Long Side Water Service Replacement with New Meter Box.
- Remove and Salvage Existing Fire Hydrants.
- Abandon Existing Water Valve as Per Specifications.
- Abandon Existing Water Line Per Specifications.
- Proposed Concrete pavement. (See Typical Single Roadway Section on Sheet 21)
- Remove and Dispose of Existing Concrete Pavement and Base Course with Curb.
- Remove and Reset Mailboxes. (Contractor to Verify if Removal is Required)
- Proposed Walkway Replacement. (See Sidewalk Details on Sheet 22)
- Proposed Pavement Header. (See Type I Paving Header Detail on Sheet 21)
- Remove Existing Storm Sewer Inlet.
- Remove Existing Storm Sewer.
- Contractor Shall Coordinate Support, Adjustment or Relocation of Power/Light Poles and/or Guy Anchors w/Owner of Poles, as Required.
- Remove and Replace Driveway with Concrete. (See Driveway Details on Sheet 22)
- Remove and Relocate Sign.
- Cut and Plug Sprinkler Head at R.O.W - No Replacement.
- Remove and Replace existing Yard Drain using 4" PVC Pipe to penetrate through Proposed Curb. (No Separate Payment)

MATCHLINE STA. 2+75 - SEE SHEET 12 FOR CONTINUATION

MATCHLINE STA. 7+25 - SEE SHEET 14 FOR CONTINUATION

Hickory Shadows Drive
(50' ROW)

Hickory Shadows Drive
(50' ROW)



MK.	DESCRIPTION	DATE	DWN.	CHK.

FOR REVIEW ONLY

JUNE 2025

NGOC KIM LE
TX. LIC. 102192
NOT FOR BIDDING
OR
CONSTRUCTION

HDR

HDR Engineering Inc. Texas Reg. No. 754
4828 Loop Central Drive, Suite 700 • Houston, Texas 77081
(713) 622-9264 • Fax (713) 622-9265 • www.hdrinc.com

City of Hilshire Village, Texas

**Hickory Shadows Drive
Paving, Drainage & Water Line Improvements**


**HICKORY SHADOWS
STA. 2+75.00 TO STA. 7+25.00**

Job No.: 10418041	Scale: HORIZ : 1" = 20' VERT : 1" = 2'	SHEET 13
Date: June, 2025	ONE INCH	
Dwn By: G.S. Fuller	IF ABOVE MARK DOES NOT MEASURE ONE INCH, THEN THIS DWG. NOT TO SCALE	OF 28
Chkd By: N. Le		


[illegible]

PROP. 7 SY CONCRETE POINT REPAIR
INCLUDING CURB, CONCRETE
PAVEMENT TO MATCH EXIST.,
AND CEMENT STABILIZED SUBGRADE
PER DETAIL SHEET 22.


- ① Proposed 1 3/4" Short Side Water Service Replacement with New Meter Box.
- ② Proposed 1 1/2" Long Side Water Service Replacement with New Meter Box.
- ③ Remove and Salvage Existing Fire Hydrants.
- ④ Abandon Existing Water Valve as Per Specifications.
- ⑤ Abandon Existing Water Line Per Specifications.
- ⑥ Proposed Concrete pavement. (See Typical Single Roadway Section on Sheet 21)
- ⑦ Remove and Dispose of Existing Concrete Pavement and Base Course with Curb.
- ⑧ Remove and Reset Mailboxes. (Contractor to Verify if Removal is Required)
- ⑨ Proposed Walkway Replacement. (See Sidewalk Details on Sheet 22)
- ⑩ Proposed Pavement Header. (See Type I Paving Header Details on Sheet 21)
- ⑪ Remove Existing Storm Sewer Inlet.
- ⑫ Remove Existing Storm Sewer.
- ⑬ Contractor Shall Coordinate Support, Adjustment or Relocation of Power/Light Poles and/or Guy Anchors w/Owner of Poles, as Required.
- ⑭ Remove and Replace Driveway with Concrete. (See Driveway Details on Sheet 22)
- ⑮ Remove and Relocate Sign.
- ⑯ Cut and Plug Sprinkler Head at R.O.W - No Replacement.
- ⑰ Remove and Replace existing Yard Drain using 4" PVC Pipe to penetrate through Proposed Curb. (No Separate Payment)



MLK	DESCRIPTION		DATE	DWN.	CHK.				
<div style="text-align: center;"> <p>FOR REVIEW ONLY JUNE 2025 NGOC KIM LE TX. LIC. 102192 NOT FOR BIDDING OR CONSTRUCTION</p> </div>									
<div style="text-align: center;"> <p>HDR Engineering Inc., Texas Reg. No. 754 4828 Loop Central Drive, Suite 700 • Houston, Texas 77081 (713) 622-9264 • Fax (713) 622-9265 • www.hdrinc.com</p> </div>									
City of Hillshire Village, Texas									
Hickory Shadows Drive									
Paving, Drainage & Water Line Improvements									
HICKORY SHADOWS									
STA. 7+25.00 TO STA. 10+50.00									
Job No.: 10418041	Scale: HORIZ : 1" = 20' VERT : 1" = 2" <div style="border: 1px solid black; padding: 2px; text-align: center;">ONE INCH</div>				SHEET <div style="font-size: 2em; font-weight: bold; text-align: center;">14</div>				
Date: June, 2025									
Dwn By: G.S. Fuller									
Ckcd By: N. Le					OF 28				




MK.	DESCRIPTION			DATE	DWN.	CHK.															
<div>HDR Engineering Inc., Texas Reg. No. 754 4828 Loop Central Drive, Suite 700 • Houston, Texas 77081 (713) 622-9264 • Fax (713) 622-9265 • www.hdrinc.com</div> <h1 style="margin-top: 20px;">HDR</h1> <p>City of Hilshire Village, Texas</p> <p>Hickory Shadows Drive Paving, Drainage & Water Line Improvement</p> <hr/> <p style="font-size: 2em;">HICKORY SHADOWS (WL)</p> <p style="font-size: 2em;">STA. -1+00.00 TO STA. 2+75.00</p> <table border="1" style="width: 100%; font-family: sans-serif;"> <tr> <td style="padding: 5px;">Job No.: I041804I</td> <td style="padding: 5px;">Scale: HORIZ : 1" = 20' VERT : 1" = 2'</td> <td style="padding: 5px; vertical-align: top;">SHEET <div style="font-size: 3em; margin: 10px 0;">15</div>OF 28</td> </tr> <tr> <td style="padding: 5px;">Date: June, 2025</td> <td style="padding: 5px; text-align: center;">[ONE INCH] <small>IF ABOVE MARK DOES NOT MEASURE ONE INCH, THEN THIS DWG. NOT TO SCALE</small></td> <td></td> </tr> <tr> <td style="padding: 5px;">Dwn By: G.S. Fuller</td> <td></td> <td></td> </tr> <tr> <td style="padding: 5px;">Chkd By: N. Le</td> <td></td> <td></td> </tr> </table>										Job No.: I041804I	Scale: HORIZ : 1" = 20' VERT : 1" = 2'	SHEET <div style="font-size: 3em; margin: 10px 0;">15</div> OF 28	Date: June, 2025	[ONE INCH] <small>IF ABOVE MARK DOES NOT MEASURE ONE INCH, THEN THIS DWG. NOT TO SCALE</small>		Dwn By: G.S. Fuller			Chkd By: N. Le		
Job No.: I041804I	Scale: HORIZ : 1" = 20' VERT : 1" = 2'	SHEET <div style="font-size: 3em; margin: 10px 0;">15</div> OF 28																			
Date: June, 2025	[ONE INCH] <small>IF ABOVE MARK DOES NOT MEASURE ONE INCH, THEN THIS DWG. NOT TO SCALE</small>																				
Dwn By: G.S. Fuller																					
Chkd By: N. Le																					



- Wirt Road
(80' ROW)
Concrete Pavement)





		
HDR Engineering Inc. Texas Reg. No. 754 4828 Loop Central Drive, Suite 700 • Houston, Texas 77081 (713) 622-9264 • Fax (713) 622-9265 • www.hdrinc.com		
<h2 style="margin: 0;">City of Hilshire Village, Texas</h2>		
<h3 style="margin: 0;">Hickory Shadows Drive</h3>		
<h3 style="margin: 0;">Paving, Drainage & Water Line Improvements</h3>		
<h2 style="margin: 0;">HICKORY SHADOWS (WL)</h2>		
<h2 style="margin: 0;">STA. 7+25.00 TO STA. 10+50.00</h2>		
Job No: IO418041	Scale: HORIZ : 1" = 20' VERT : 1" = 2" <div style="border: 1px solid black; padding: 2px; text-align: center; margin: 5px 0;"> ONE INCH </div> <small>IF ABOVE HARN DOES NOT MEASURE ONE INCH, THEN THIS DRAW. NOT TO SCALE</small>	SHEET <div style="font-size: 2em; font-weight: bold; text-align: center;">17</div>
Date: June, 2025	OF 28	
Dwn By: G.S. Fuller		
Chkd By: N. Le		



IMPROVEMENTS LEGEND:
UTILITIES, PAVING & DRAINAGE:

- 1 Proposed 1 1/2" Short Side Water Service Replacement with New Meter Box.
- 2 Proposed 1 1/2" Long Side Water Service Replacement with New Meter Box.
- 3 Remove and Salvage Existing Fire Hydrants.
- 4 Abandon Existing Water Valve as Per Specifications.
- 5 Abandon Existing Water Line Per Specifications.
- 6 Proposed Concrete pavement. (See Typical Single Roadway Section on Sheet 21)
- 7 Remove and Dispose of Existing Concrete Pavement and Base Course with Curb.
- 8 Remove and Reset Mailboxes. (Contractor to Verify if Removal is Required)
- 9 Proposed Walkway Replacement. (See Sidewalk Details on Sheet 22)
- 10 Proposed Pavement Header. (See Type I Paving Header Detail on Sheet 21)
- 11 Remove Existing Storm Sewer Inlet.
- 12 Remove Existing Storm Sewer.
- 13 Contractor Shall Coordinate Support, Adjustment or Relocation of Power/Light Poles and/or Guy Anchors w/Owner of Poles, as Required.
- 14 Remove and Replace Driveway with Concrete. (See Driveway Details on Sheet 22)
- 15 Remove and Relocate Sign.
- 16 Cut and Plug Sprinkler Head at R.O.W - No Replacement.
- 17 Remove and Replace existing Yard Drain using 4" PVC Pipe to penetrate through Proposed Curb. (No Separate Payment)



MK.	DESCRIPTION	DATE	DWN.	CHK.

FOR REVIEW ONLY

JUNE 2025

NGOC KIM LE

TX. LIC. 102192

NOT FOR BIDDING OR CONSTRUCTION

HDR


HDR Engineering Inc. Texas Reg. No. 754
4828 Loop Central Drive, Suite 700 • Houston, Texas 77081
(713) 622-9264 • Fax (713) 622-9265 • www.hdrinc.com

City of Hilshire Village, Texas


**Hickory Shadows Drive
Paving, Drainage & Water Line Improvements**

**HICKORY SHADOWS -
(WATER LINE EASEMENT)**

Job No.: 10418041	Scale: HORIZ : 1" = 20' VERT : 1" = 2'	18 OF 28
Date: June, 2025	ONE INCH	
Dwn By: G.S. Fuller	IF ABOVE MARK DOES NOT MEASURE ONE INCH, THEN THIS DWG. NOT TO SCALE	
Chkd By: N. Le		



- NOTES:
1. ALL STORM WATER POLLUTION PREVENTION FEATURES APPLIED FOR EXISTING CONDITIONS SHALL REMAIN IN EFFECT THROUGHOUT CONSTRUCTION PROGRESS AS REQUIRED.
 2. ALL SWPPP FEATURE LOCATIONS ARE APPROXIMATE. CONTRACTOR SHALL VERIFY EXISTING CONDITIONS IN THE FIELD AND ADJUST AS REQUIRED TO ASSURE COMPLIANCE WITH SWPPP SPECIFICATIONS INCLUDING PROTECTION OF PRIVATE PROPERTIES.
 3. INLET PROTECTION BARRIERS SHALL BE INSTALLED FOR EXISTING AND PROPOSED SITUATIONS AS REQUIRED.



SW3P LEGEND

- 60" EXISTING STORM SEWER
- 60" PROPOSED STORM SEWER
- EXISTING MANHOLE
- EXISTING "C" INLET
- PROPOSED "C" INLET
- PROPOSED "BB" INLET
- PROPOSED JUNCTION BOX
- IPB INLET PROTECTION BARRIER FOR EXIST. AND PROP. INLETS
- ROW IN PROJECT AREA

MK.	DESCRIPTION	DATE	DWN.	CHK.

FOR REVIEW ONLY

JUNE 2025

NGOC KIM LE

TX. LIC. 102192

NOT FOR BIDDING OR CONSTRUCTION

HDR


HDR Engineering Inc. Texas Reg. No. 754
4828 Loop Central Drive, Suite 700 • Houston, Texas 77081
(713) 622-9264 • Fax (713) 622-9265 • www.hdrinc.com

City of Hilshire Village, Texas

Hickory Shadows Drive
Paving, Drainage & Water Line Improvements


SWPPP Plan

Job No.: 10418041	Scale: HORZ : 1" = 30'	SHEET 19 OF 28
Date: June, 2025	VERT : ONE INCH	
Dwn By: G.S. Fuller	IF ABOVE MARK DOES NOT MEASURE ONE INCH, THEN THIS DWG. NOT TO SCALE	
Chkd By: N. Le		






CONSTRUCTION NOTES:

1. SET 2 INCH BY 2 INCH WOODEN STAKES SPACED A MAX OF 6 FEET APART AND EMBEDDED A MIN OF 12 INCHES.
2. WOVEN WIRE FENCE TO BE FASTENED SECURELY TO FENCE POSTS WITH STAPLES.
3. FILTER CLOTH TO BE FASTENED SECURELY TO WOVEN WIRE FENCE, WITH TIES SPACED EVERY 24 INCHES AT TOP AND MIDSECTION.
4. MINIMUM HEIGHT OF FILTER SHOULD BE 18 INCHES AND A MAXIMUM OF 36 INCHES ABOVE NATURAL GROUND.
5. WHEN TWO SECTIONS OF FILTER CLOTH ADJOIN EACH OTHER THEY SHALL BE OVERLAPPED 6 INCHES AT THE POSTS, AND FOLDED.
6. SEE SPECIFICATION FOR FILTER FABRIC BARRIER.



REINFORCED FILTER FABRIC BARRIER





CONSTRUCTION NOTES:

1. LENGTH SHALL BE AS SHOWN ON THE CONSTRUCTION DRAWINGS, BUT NOT LESS THAN 50 FEET.
2. THICKNESS SHALL BE NOT LESS THAN 6 INCHES.
3. WIDTH SHALL BE NOT LESS THAN FULL WIDTH OF ALL POINTS OF INGRESS OR EGRESS.
4. STABILIZATION FOR OTHER AREAS SHALL HAVE THE SAME AGGREGATE THICKNESS AND WIDTH REQUIREMENTS AS THE STABILIZED CONSTRUCTION EXT, UNLESS OTHERWISE SHOWN ON THE CONSTRUCTION DRAWINGS.
5. STABILIZED AREA MAY BE WIDENED OR LENGTHENED TO ACCOMMODATE A TRUCK WASHING AREA. AN OUTLET SEDIMENT TRAP MUST BE PROVIDED FOR THE TRUCK WASHING AREA.
6. SEE SPECIFICATION FOR STABILIZED CONSTRUCTION EXT.
7. STABILIZED CONSTRUCTION EXT SHALL BE MAINTAINED FREE OF SEDIMENT FOR THE DURATION OF THE PROJECT.

CONSTRUCTION NOTE:

1. MAX. POST SPACING SHALL BE 4 FEET. ADDITIONAL POSTS MAY BE ADDED. POSTS SHALL BE PLACED ON EACH CORNER, AS A MINIMUM, AS SHOWN.
2. PLACEMENT OF FILTER FABRIC BARRIER FROM INLET SHALL VARY ACCORDING TO SITE CONDITIONS. TYPICAL PLACEMENT SHALL BE 36" MINIMUM FROM INLET EDGE.



MK.	DESCRIPTION	DATE	DWN.	CHK.

FOR REVIEW ONLY

JUNE 2025

NGOC KIM LE

TX LIC. 102192

NOT FOR BIDDING OR CONSTRUCTION

HDR


HDR Engineering Inc. Texas Reg. No. 754
4828 Loop Central Drive, Suite 700 • Houston, Texas 77081
(713) 622-9264 • Fax (713) 622-9265 • www.hdrinc.com

City of Hilshire Village, Texas

Hickory Shadows Drive
Paving, Drainage & Water Line Improvements


SWPPP DETAILS I

Job No.: 10418041	Scale: HORZ : VERT : 1" = 10'	SHEET 20 OF 28
Date: June, 2025		
Dwn By: G.S. Fuller		
Chkd By: N. Le		




CONCRETE CURB

- ## TYPICAL SINGLE ROADWAY SECTION



TYPE I PAVING HEADER DETAIL



MK.	DESCRIPTION					DATE	DWN.	CHK.	
<div>HDR</div> <p>HDR Engineering Inc. Texas Reg. No. 754 4828 Loop Central Drive, Suite 700 • Houston, Texas 77081 (713) 622-9264 • Fax (713) 622-9265 • www.hdrinc.com</p>									
City of Hickshire Village, Texas									
Hickory Shadows Drive Paving, Drainage & Water Line Improvements									
PAVING DETAILS 1									
Job No.: I04I804I	Scale: HORZ : VERT : [ONE INCH] IF ABOVE MARK DOES NOT MEASURE ONE INCH, THEN THIS MARK NOT TO SCALE					SHEET <div>21</div> OF 28			
Date: June, 2025									
Dwn By: G.S. Fuller									
Chkd By: N. Le									





- ## DRIVEWAY NOTES

1. DRIVEWAYS SHALL BE CONSTRUCTED TO MATCH EXISTING DRIVEWAY WIDTH MEASURED AT THE RIGHT-OF-WAY. WHEN DRIVEWAY EXCEEDS 20'-0" IN WIDTH, OR WHEN EXISTING DRIVEWAY JOINT OR PROPOSED PAVING JOINT FALLS WITHIN LIMIT OF DRIVEWAY, A 3/4" REDWOOD BOARD EXPANSION JOINT W/STEEL RUNNING THROUGH IT, OR APPROVED EQUAL SHALL BE INSTALLED THE FULL LENGTH OF THE DRIVEWAY.
2. RESIDENTIAL DRIVEWAYS SHALL BE CONSTRUCTED OF CONCRETE 6" THICK.
3. SELECT BACKFILL SHALL BE USED AS A BASE LEVELER AND/OR AS BACKFILL REQUIRED WHEN OVER EXCAVATION OCCURS DUE TO POOR SOILS OR ANY OTHER CONDITION RESULTING IN OVER EXCAVATION OF DRIVEWAYS. SELECT BACKFILL SHALL BE COMPACTED TO 95% STANDARD PROCTOR DENSITY.
4. WHERE TYING INTO EXISTING CONCRETE DRIVEWAY AND CONDITION OF EXISTING DRIVEWAY ALLOWS, PROVIDE 3/4" REDWOOD BOARD W/24" LONG #4 DEFORMED BARS @ 18" O.C. THROUGH IT DRILLED INTO EXISTING DRIVEWAY. WHERE EXISTING CONCRETE IS IN POOR CONDITION OR WHERE DRIVEWAY IS ASPHALT, SHELLCRETE, SHELL, GRAVEL, DIRT, OR GRASS, PROVIDE STANDARD PAVING HEADER AT NO ADDITIONAL COST.
5. THE PROPOSED LIMITS OF REPLACEMENT OF DRIVEWAYS SHOWN ON THE PLAND AND PROFILES ARE APPROXIMATE. CONTRACTOR TO VERIFY THAT BASED ON THESE LIMITS, THE SLOPE IS NOT GREATER THAN 12%. CONTRACTOR SHALL COORDINATE WITH THE CITY'S REPRESENTATIVE AND PROPERTY OWNER TO REMOVE AND REPLACE DRIVEWAY BEYOND ROW AS REQUIRED TO ACHIEVE DRIVEWAY GRADE EQUAL TO OR LESS THAN 12%. REMOVAL/REPLACEMENT OF DRIVEWAYS TO RIGHT-OF-WAY VS NEAREST JOINT BEYOND ROW SHALL BE A FIELD DECISION. CITY REQUIRES CLEAN JOINT AT ROW IN ANY CASE. IF DECISION IS MADE TO EXTEND DRIVEWAY REPLACEMENT TO AN EXISTING EXPANSION JOINT BEYOND THE ROW, PROVISION OF A CONTRACTION JOINT AT THE ROW IS REQUIRED.


WK.	DESCRIPTION		DATE	DWN.	CHK.		
							
 <p style="margin-top: 10px;"> HDR Engineering Inc. Texas Reg. No. 754 4828 Loop Central Drive, Suite 700 • Houston, Texas 77081 (713) 622-9264 • Fax (713) 622-9265 • www.hdrinc.com </p>							
<h2 style="margin: 0;">City of Hilshire Village, Texas</h2>							
<h3 style="margin: 0;">Hickory Shadows Drive</h3> <h3 style="margin: 0;">Paving, Drainage & Water Line Improvements</h3>							
<h2 style="margin: 0;">PAVING DETAILS II</h2>							
Job No.: 10418041				Scale: _____ HORIZ : _____ VERT : _____ <div style="border: 1px solid black; padding: 2px; text-align: center; margin-top: 5px;"> ONE INCH </div>		SHEET <div style="font-size: 2em; font-weight: bold; margin: 10px 0;">22</div>	
Date: June, 2025				IF ABOVE MARK DOES NOT MEASURE ONE INCH, THEN THIS DWG. NOT TO SCALE		OF 28	
Dwn By: G.S. Fuller							
Chkd By: N. Le							

MANHOLE FRAME & COVER SHALL USE EAST JORDAN IRON WORKS W/"CITY OF HILSHIRE VILLAGE" AND "STORM SEWER" FORGED IN FRAMES WITH MUDRINGS. (SEE MANHOLE PAVEMENT DETAIL)

E5 BARS IN ADDITION TO PAVEMENT REINFORCING.




TEMPORARY TIMBER COVER




PRECAST STORM SEWER JUNCTION BOX NOTES:

- All Precast Storm Box Manholes Shall Be Constructed Of 4000 Psi Concrete, Reinforced 60000 Psi Hs 20 Loading.
- Where Storm Sewer Lead & Trunkmain Depths Allow The Top Of The Box To Be At Or Greater Than A Min. 4'-0" Depth, Cone Sections May Be Used. Where Leads & Main Depths Require The Box Manhole Top To Be Less Than 4'-0", Contractor shall use flat top and rings.
- In Cases Where The Top Slabs May Encroach Into Proposed Pavement Subgrade, The Subgrade Over The Box Shall Be Eliminated And The Proposed Concrete Pavement Shall Be Poured In Required Extra Thickness To The Top Of The Box As Noted On This Sheet.
- Top And Bottom Slabs Along With Wall Thickness And Related Structural Steel Including cones or flat top and rings, Shall Be Per Manufacturer, signed and sealed by an Engineer licensed in the state of Texas for each proposed junction box on the plans. Provide location with street name, Station and Offset.



BEDDING AND BACKFILL DETAIL FOR STORM SEWER PIPES UNDER PAVEMENT AND UNDER NATURAL GROUND

NOT TO SCALE



WET CONDITION BEDDING FOR STORM SEWER PIPE INSTALLATION

NOT TO SCALE

GENERAL NOTES:


- TRENCH EXCAVATION, BEDDING & BACKFILL COSTS ARE INCIDENTAL TO PIPE INSTALLATION AND ARE BASED ON THE LIMITS SHOWN IN THESE DETAILS. ANY COST INCURRED FOR AREAS EXCAVATED AND OR REQUIRING BACKFILL BEYOND THESE LIMITS RESULTING FROM CONTRACTORS FAILURE TO CONTROL THESE LIMITS SHALL BE BORNE BY THE CONTRACTOR.
- MAX TRENCH WIDTH SHALL NOT BE GREATER THAN MIN TRENCH WIDTH PLUS 24". UNLESS OTHERWISE NOTED.
- IF OUTSIDE EDGE OF PIPE IS WITHIN 3' OF BACK OF CURB, BACKFILL SHALL BE PERFORMED AS UNDER PAVEMENT.

BEDDING AND BACKFILL NOTES FOR STORM SEWER INSTALLATION:

- A. MIN. TRENCH WIDTH SHALL BE PIPE O.D. PLUS AN ALLOWANCE "A" FOR THE NOMINAL PIPE SIZE:
- | | |
|-------------------|-----|
| NOMINAL PIPE SIZE | "A" |
| <18" | 24" |
| 18" TO 30" | 24" |
| >30" | 36" |
- B. CEMENT STABILIZED SAND (1:1 SACKS OF CEMENT PER TON, COMPACTED TO AT LEAST 95% OF MAX. STD. PROCTOR) PLACED BEFORE PIPE IS LAID UP TO FLOW LINE OF PIPE OR ABOVE - MINIMUM DEPTH = 12".
- C. CEMENT STABILIZED SAND (AS SPECIFIED ABOVE) THOROUGHLY RODDED, PLACED AFTER PIPE IS LAID.
- D. CEMENT STABILIZED SAND TO 12-IN BELOW TOP OF SUBGRADE.
- E. SELECT EARTH BACKFILL WITH MAX LIQUID LIMIT OF 40, MIN. P.I. OF 7, MAX P.I. OF 20 CONTAINING NO ROCKS OR OTHER DEBRIS NOR CONTAINING ANY DIRT CLODS EXCEEDING 6" IN ANY DIMENSION. PLACED IN 6" LAYERS, MOISTENED IF NECESSARY AND THOROUGHLY COMPACTED TO 95% DENSITY AS DETERMINED BY BY ASTM D698, UNLESS OTHERWISE NOTED. IN SITU SOILS MAY BE UTILIZE ONLY IF IT MEETS THIS CRITERIA AND SUITABLE MATERIAL CLASSIFICATION PER THE SPECIFICATIONS.
- F. IN THE EVENT DIMENSION IS LESS THAN 8", CEMENT STABILIZED SAND SHALL BE EXTENDED TO BOTTOM OF CONCRETE.

SODDING NOTES FOR STORM SEWER INSTALLATION:

- SODDING SHALL BE INSTALLED IN AREAS DISTURBED BY CONSTRUCTION.
- CONTRACTOR SHALL REPLACE SODDING IN AREAS DAMAGED BY CONSTRUCTION AND THE REPLACEMENT SHALL BE CONSIDERED INCIDENTAL TO THE PROJECT.
- IF EXISTING LANDSCAPING OTHER THAN GRASS IS WITHIN THESE AREAS, THE CONTRACTOR SHALL REBUILD OR REINSTALL THE LANDSCAPING PER THE PERTINENT BID ITEM.



PRECAST STORM SEWER JUNCTION BOX (JCTBOX(COMPL)(PJB))

MK.	DESCRIPTION	DATE	DWN.	CHK.



HDR Engineering Inc. Texas Reg. No. 754
4828 Loop Central Drive, Suite 700 • Houston, Texas 77081
(713) 622-9264 • Fax (713) 622-9265 • www.hdrinc.com

City of Hilshire Village, Texas

Hickory Shadows Drive
Paving, Drainage & Water Line Improvements

STORM SEWER DETAILS I


Job No.: 10418041
Date: June, 2025
Dwn By: G.S. Fuller
Chld By: N. Le

Scale:
HORZ :
VERT :
ONE INCH
IF ABOVE MARK DOES NOT
MEASURE ONE INCH, THEN
THIS DWG. NOT TO SCALE

SHEET


23

OF 28



NOTES:
USE CAST IRON FRAME AND PLATE (PER SPECIFICATIONS). LEAD SHALL LEAVE INLET AT LOCATION AND GRADE REQUIRED. BRICK INLETS ARE NOT PERMITTED.


BAR LIST				
No.	Size	Length	Shp.	Loc.
4	#4	5'-10"	St.	Horiz.
7	#4	0'-10"	St.	Vert.
7	#3	1'-6"	Bt.	




NOTE:
TYPE B-B INLETS SHALL INCLUDE SOLID PLATE, NO GRATES (TYP.)

TYPE B-B INLET

SCALE: NTS




PLAN




GUTTER DEPRESSIONS FOR TYPE B-B INLET

SCALE: NTS




SECTION THRU "I" BEAM




HALF FRONT ELEVATION

PRECAST CURB BEAM




TRANS SECTION




EXTENSION

PLAN


INLET



EXTENSION




ELEVATION




SECTION B-B

GENERAL NOTES:

- All concrete shall be Class A. All exposed corners shall be chamfered 3/4". Pipes shall enter inlets as shown elsewhere on plans. Slope top of inlets as directed to match graded section.
- All materials used in casting manhole covers and ladder rung shall conform to A.S.T.M. Specifications.
- A permissible construction joint may be placed in the inlet wall with the approval of the Engineer.
- Manhole ring and cover shall be 23 1/2" unless otherwise specified in the plans. Connection of pipes to precast units shall be mortared as directed by the Engineer. * But not less than six inches over highest pipe.
- Control points for horizontal layout of inlets, all types, is the lateral center of the inlet, without regard for extensions, at the back of curb.
- 5' Extension is not included unless called for in plans.




AT CURB




YARD DRAIN CONNECTION DETAIL

NOT TO SCALE




THROAT DETAIL



BACK OPENING DETAIL

Note: This is to be used only where specified in plans.




SECTION A-A

TYPE "C" INLET DETAILS

NOT TO SCALE

MK.	DESCRIPTION	DATE	DWN.	CHK.



HDR Engineering Inc. Texas Reg. No. 754
4828 Loop Central Drive, Suite 700 • Houston, Texas 77081
(713) 622-9264 • Fax (713) 622-9265 • www.hdrinc.com

City of Hilshire Village, Texas

Hickory Shadows Drive
Paving, Drainage & Water Line Improvements

STORM SEWER DETAILS II


Job No.: 10418041
Date: June, 2025
Dwn By: G.S. Fuller
Chd By: N. Le

Scale:
HORIZ :
VERT :
ONE INCH
IF ABOVE MARK DOES NOT
MEASURE ONE INCH, THEN
THIS DWG. NOT TO SCALE


SHEET

24


OF 28




FITTING ASSEMBLY & THRUST BLOCK DETAIL
NOT TO SCALE



THRUST BLOCKING OF IN LINE VALVE DETAIL
NOT TO SCALE




MECHANICAL RESTRAINT DETAIL
NOT TO SCALE



FRONT ELEVATION
GATE VALVE INSTALLATION DETAIL
NOT TO SCALE


SIDE ELEVATION



PROPOSED WATERLINE VERTICAL CLEARANCE TABLE		
OBSTRUCTION	MINIMUM CLEARANCE	MATERIAL
SANITARY SEWER	SEE TCEQ REGULATIONS (SPEC SECTIONS 02664)	SEE TCEQ REGULATIONS (SPEC SECTIONS 02664)
PRIVATE UTILITY	12"	C-900 DR 18 PVC *
PRIVATE PIPELINE	24"	C-900 DR 18 PVC *
WATERLINE	6"	C-900 DR 18 PVC *
STORM SEWER	6"	C-900 DR 18 PVC *

* IF DEPTH OF WATERLINE IS GREATER THAN 8' OR COVER IS LESS THAN 3' MATERIAL SHALL BE C-900 DR 14 PVC.


CLEARANCE DETAIL
NOT TO SCALE



STANDARD FIRE HYDRANT DETAIL
NOT TO SCALE

FIRE HYDRANT NOTES

- ALL FIRE HYDRANTS SHALL CONFORM TO THE CITY'S FIRE DEPARTMENT REQUIREMENTS.
- ALL FIRE HYDRANTS SHALL BE LOCATED 3' BACK OF CURB FOR CURB AND GUTTER STREETS AND 3' INSIDE RIGHT-OF-WAY (2' ABSOLUTE MIN) FOR ROADSIDE DITCH STREETS.
- FIRE HYDRANTS SHOWN AT INTERSECTIONS SHALL BE LOCATED AT THE CURB RETURN FOR CURB AND GUTTER STREETS AND AT THE PROPERTY CORNER FOR ROADSIDE DITCH STREETS UNLESS OTHERWISE SHOWN ON PLANS AND APPROVED BY OWNER.
- ALL FIRE HYDRANTS SHALL HAVE A MINIMUM OF 5'-0" LEAD PIPE. LEAD PIPES SHALL NOT EXCEED 100' IN LENGTH AND SHALL HAVE NO VERTICAL OR HORIZONTAL BENDS.
- EACH FIRE HYDRANT LEAD SHALL HAVE A VALVE, PER SPECIFICATIONS, BEING EITHER A GATE VALVE WITH A TEE CONNECTION TO THE MAIN OR A TAPPING SLEEVE AND VALVE CONNECTION TO THE MAIN.
- VALVES SHALL NOT BE LOCATED AT THE FLOWLINE OF ANY DITCH.
- NEW FIRE HYDRANTS REPLACING THOSE TO BE SALVAGED SHALL BE PLACED 2'± EITHER SIDE OF THE EXISTING.
- FIRE HYDRANTS SHALL BE PLACED AS SHOWN ON PLANS
- FIRE HYDRANTS LOCATED IN AREAS OTHER THAN INTERSECTIONS SHALL BE LOCATED AT SIDE OF LOT LINES, UNLESS SHOWN OTHERWISE ON PLANS AND APPROVED BY OWNER.
- NEW FIRE HYDRANTS SHALL BE LOCATED IN ALL AREAS WHERE EXISTING FIRE HYDRANTS ARE TO BE SALVAGED.
- IN THE EVENT THAT A PROPOSED FIRE HYDRANT CANNOT BE LOCATED IN AREA DESCRIBED AS TYPICAL, ULTIMATE LOCATION OF FIRE HYDRANTS SHALL BE AS DETERMINED BY OWNER.
- ALL FIRE HYDRANTS SHALL BE INSTALLED WITH 5" STORZ ADAPTERS WITH CAP.
- STORZ ADAPTERS SHALL BE AS MANUFACTURED BY HARRINGTON HPHA50-40NH/CAP STORZ PERMANENT HYDRANT ADAPTER WITH CAP (HYDRANT CONVERTER) OR FYRELANE ADPT-5.0ST-BC 5" STORZ BLIND CAP (ALUMINUM).
- NO PART OF THE STORZ ADAPTERS SHOULD BE PAINTED. ALL PARTS ARE DESIGNED TO PROVIDE FUNCTION WITHOUT PAINT. THIS INCLUDES SOME WITH THE CONNECTING CABLE THAT HAS BUILT-IN REFLECTORS FOR BETTER RECOGNITION AT NIGHT.



HORIZ/ VERT

HORIZ/ VERT

THRUST BLOCKING NOTES:

- SIZE OF THRUST BLOCK TO BE ADEQUATE FOR TWO TIMES, TEST PRESSURE; THAT IS 250 PSI NO SEPARATE PAY FOR THRUST BLOCKING.
- RESTRAINED JOINT PIPING SHALL BE USED IN ALL AREAS WHERE HORIZONTAL NEW PIPE HAS LESS THAN 4' COVER. ALL VERTICAL BENDS SHALL HAVE RESTRAINED JOINTS.


JOINT RESTRAINT DETAILS
NOT TO SCALE

MK.	DESCRIPTION	DATE	DWN.	CHK.
<div>FOR REVIEW ONLY JUNE 2025 NGOC KIM LE TX LIC. 102192 NOT FOR BIDDING OR CONSTRUCTION</div>				
<div>HDR HDR Engineering Inc. Texas Reg. No. 754 4828 Loop Central Drive, Suite 700 • Houston, Texas 77081 (713) 622-9264 • Fax (713) 622-9265 • www.hdrinc.com</div>				
City of Hilshire Village, Texas				
Hickory Shadows Drive Paving, Drainage & Water Line Improvements				
WATER LINE DETAILS I				
Job No.: 10418041	Scale: HORIZ : VERT : ONE INCH	SHEET 25 OF 28		
Date: June, 2025	IF ABOVE MARK DOES NOT MEASURE ONE INCH, THEN THIS DWG. NOT TO SCALE			
Dwn By: G.S. Fuller				
Chld By: N. Le				



1. TAPS MUST BE SPACED A MIN OF ONE FOOT APART WHEN STAGGERED ON OPPOSITE SIDE OF THE WATERLINE, AND MUST BE SPACED A MIN OF TWO FEET APART WHEN ON SAME SIDE OF WATERLINE.
2. FIELD VERIFY SIZE AND LINE TYPE (COPPER, GALV. STL., PLASTIC, ETC.) OF EXIST. FOR THE PROPER CONNECTION TO CURB STOPS AND FOR APPROPRIATE PACK JOINT COUPLING IF APPLICABLE.
3. INSTALL ALL SERVICE LINE RECONNECTS OR NEW SERVICE PERPENDICULAR TO PROPOSED MAINLINE.
4. NEW OR MODIFICATION TO LONG SIDE SERVICE TO BE AUGERED UNDER PMVT UNLESS APPROVED IN WRITING BY THE CITY.

NOT TO SCALE



BEDDING NOTES:

- A. BANK SAND PLACED BEFORE PIPE IS LAID.
- B. BANK SAND PLACED AFTER PIPE IS LAID, THOROUGHLY RODDED AND MECHANICALLY TAMPED TO MIN 95% OF MAX. DRY DENSITY AS DETERMINED BY ASTM-D 6 98
- C. SELECT EARTH BACKFILL, MAX LIQUID LIMIT OF 40, MIN P.I. 7, MAX P.I. 20 CONTAINING NO ROCKS OR OTHER DEBRIS NOR CONTAINING ANY DIRT CLOTS EXCEEDING 6" IN ANY DIMENSION. PLACED IN 6" LAYERS, MOISTENED IF NECESSARY AND THOROUGHLY COMPACTED TO A DENSITY EQUIVALENT TO THAT OF SURROUNDING UNDISTURBED SOIL, UNLESS OTHERWISE NOTED.
- D. CEMENT STABILIZED SAND (AS PER SPECIFICATIONS)

WATER/SANITARY FORCE MAIN PIPE TRENCH
DETAIL - FOR PIPES UNDER NATURAL GROUND

SODDING NOTES:


1. SODDING SHALL BE INSTALLED IN AREAS DISTURBED BY CONSTRUCTION.
2. CONTRACTOR SHALL REPLACE SODDING IN AREAS DAMAGED BY CONSTRUCTION AND THE REPLACEMENT SHALL BE CONSIDERED INCIDENTAL TO THE PROJECT.
3. IF EXIST LANDSCAPING OTHER THAN GRASS IS WITHIN THESE AREAS, THE CONTRACTOR SHALL REBUILD OR REINSTALL THE LANDSCAPING OF THE AREA AFTER CONSTRUCTION IN AN EQUAL OR BETTER CONDITION.

NOT TO SCALE




1. PLACE GATE VALVE HORIZONTAL TO GROUND WITH END OF BRASS PLUG 3 INCHES FROM SURFACE.
2. PLACE METER BOX CENTERED AROUND GATE VALVE BODY WITH LONG SIDE PARALLEL TO VALVE.

NOT TO SCALE



NOT TO SCALE



TYPICAL SECTION

NOTES:

1. SODDING SHALL BE ON AREAS DISTURBED BY CONSTRUCTION.
2. SODDING LIMITS AT DITCHES SHALL BE THOSE AREAS DISTURBED BY THE GRADING PROCESS.
3. CONTRACTOR TO REPAIR SODDING IN THE AREAS DAMAGED BY CONSTRUCTION AND SHALL BE CONSIDERED INCIDENTAL TO THE PROJECT COST.
4. IN THE EVENT EXIST LANDSCAPING OTHER THAN GRASS IS WITHIN THESE AREAS, THE CONTRACTOR SHALL REBUILD OR REINSTALL THE LANDSCAPING OF THE AREA AFTER CONSTRUCTION IN AN EQUAL OR BETTER CONDITION.

NOT TO SCALE

MK.	DESCRIPTION	DATE	DWN.	CHK.




HDR Engineering Inc. Texas Reg. No. 754
1828 Loop Central Drive, Suite 700 • Houston, Texas 77081
(713) 622-9264 • Fax (713) 622-9265 • www.hdrinc.com

Hickory Shadows Drive
Paving, Drainage & Water Line Improvements


WATER LINE DETAILS II

Job No.: 10418041	Scale: HORIZ :	SHEET
Date: June, 2025	VERT :	26
Dwn By: G.S. Fuller	ONE INCH	
Chkd By: N. Le	IF ABOVE MARK DOES NOT MEASURE ONE INCH, THEN THIS DWG. NOT TO SCALE	OF 28



Tree No.	Location	Description	Comments	Treatment
1	Park	24" Live Oak	Harris County Tree, Not impacted	
2	Park	5" Yaupon	Harris County Tree, Not impacted	
3	11 Hickory Shadows	16" Bradford Pear	50% canopy dieback, Poor	Root prune irrigation tie-in, Fence, Clearance prune
4	11 Hickory Shadows	4' Sago		Fence
5	11 Hickory Shadows	2" Crepe Myrtle	Topped	Fence
6	11 Hickory Shadows	10" Crepe Myrtle	Topped	Fence
7	11 Hickory Shadows	5" Crepe Myrtle	Topped	Fence
8	11 Hickory Shadows	5' Sago		Fence
9	11 Hickory Shadows	5" Crepe Myrtle	Topped	Fence
10	11 Hickory Shadows	3" Crepe Myrtle	Topped	Fence
11	11 Hickory Shadows	10" Crepe Myrtle	Topped	Fence
12	11 Hickory Shadows	6' Sago		Fence, Clearance prune
13	11 Hickory Shadows	7" Crepe Myrtle	Topped	Fence, Clearance prune
14	11 Hickory Shadows	8" Crepe Myrtle	Topped	Fence
15	13 Hickory Shadows	15" Water Oak	Private tree	Hand dig water service from curb to meter, Fence, Clearance prune
16	13 Hickory Shadows	7" Crepe Myrtle	Topped	Fence
17	13 Hickory Shadows	38" Live Oak	Private tree	Root prune water service from curb to meter, Fence, Clearance prune
18	18 Hickory Shadows	26" Live Oak	Pruned by CPE, Private tree	Root prune for bends, Fence, Root stimulate
19	18 Hickory Shadows	15" Live Oak	Suppressed by lager Live Oak	Root prune for bends, Fence, Bore waterline, Clearance prune, Root stimulate
20	18 Hickory Shadows	7' Sago Palm		Fence, Bore waterline, Clearance prune
21	18 Hickory Shadows	5' Sago		Fence, Bore waterline, Clearance prune
22	18 Hickory Shadows	16" Live Oak	Private tree	Root prune for tee and tap, Hand dig service lead tap to meter, Fence, Bore waterline, Clearance prune, Root stimulate

Tree No.	Location	Description	Comments	Treatment
23	20 Hickory Shadows	9' Sago		Bore waterline, Fence
24	20 Hickory Shadows	6' Sago		Bore waterline, Fence
25	22 Hickory Shadows	11" Chinese Pistache	Private tree	Fence, Bore waterline, Clearance prune
26	24 Hickory Shadows	5" Shumard Oak		Root prune for fire hydrant, Fence, Bore waterline
27	24 Hickory Shadows	5" Pittosporum	Private tree, Not impacted	
28	24 Hickory Shadows	6" Ligustrum	Private tree, Not impacted	
29	24 Hickory Shadows	19" Live Oak	Private tree, Not impacted	
30	24 Hickory Shadows	3" Red Maple	Private tree	Fence
31	9 Hickory Shadows	22" Live Oak		Hand dig water service from curb to meter, Fence, Clearance prune
32	7 Hickory Shadows	16" Hickory	50% dieback, Private, Not impacted	
33	7 Hickory Shadows	20" Live Oak	30% canopy dieback	Hand root prune back side of proposed inlet during excavation, Do not disturb more than 4" back of proposed inlet, Fence, Root stimulate, Clearance prune
34	7 Hickory Shadows	2" Cherrylaurel		Fence
35	7 Hickory Shadows	23" Live Oak	Interior foliage stripped, 25% canopy dieback	Remove fire hydrant bonnet, cut stem and barrel 6" below grade. Remove valve box and backfill. Do not excavate to remove entire fire hydrant. Do not cut roots greater than 1" in diameter. Hand dig for new fire hydrant, Fence, Root prune for bends, Root stimulate, Clearance prune
36	7 Hickory Shadows	23" Live Oak	20% dieback	Hand dig tap&lead, Fence, Bore waterline, Root prune for bends, Root stimulate, Clearance prune
37	7 Hickory Shadows	9" Crepe Myrtle		Bore waterline, Fence
38	17 Hickory Shadows	12" Little Gem Magnolia	Base of trunk growing over existing driveway, Remove for drive replacement	Remove tree
39	19 Hickory Shadows	6" Crepe Myrtle	Topped, Private, Not impacted	
40	19 Hickory Shadows	3' Yucca	Remove for bends	Remove tree
41	19 Hickory Shadows	9" Crepe Myrtle	Remove for bends	Remove tree
42	21 Hickory Shadows	25" Live Oak	Private tree	Root prune for waterline, Fence
43	21 Hickory Shadows	17" Live Oak	Suppressed by lager Live Oak, 30% dieback	Root prune for waterline, Fence, Root stimulate
44	21 Hickory Shadows	22" Magnolia	30% dieback, Private tree	Root prune tap&lead, Fence, Bore waterline
45	16 Hickory Shadows	9" Fringe Tree		Hand dig tap& lead, Fence, Bore waterline, Clearance prune
46	16 Hickory Shadows	27" Live Oak	Private tree	Root prune for tap&lead, Fence, Bore waterline, Clearance prune
47	16 Hickory Shadows	9" Fringe Tree		Hand dig tap&lead, Fence, Bore waterline, Clearance prune
48	16 Hickory Shadows	8" Little Gem Magnolia		Fence, Bore waterline, Clearance prune
49	14 Hickory Shadows	8" Little Gem Magnolia		Root prune for inlet, Fence, Bore waterline, Clearance prune
50	14 Hickory Shadows	12" Crepe Myrtle	Topped	Bore waterline, Fence
51	14 Hickory Shadows	4" Little Gem Magnolia		Bore waterline, Fence
52	14 Hickory Shadows	8" Camphor	Remove for bends	Remove tree
53	12 Hickory Shadows	15" Crepe Myrtle	Remove for bends	Remove tree
54	12 Hickory Shadows	9" Crepe Myrtle	Remove for bends	Remove tree
55	12 Hickory Shadows	37" Live Oak	Private tree, Not impacted	
56	12 Hickory Shadows	2" Saucer Magnolia	Remove for bends	Remove tree
57	12 Hickory Shadows	2" Saucer Magnolia	Remove for bends	Remove tree
58	12 Hickory Shadows	2" Saucer Magnolia	Remove for bends	Remove tree
59	10 Hickory Shadows	21" Live Oak		Fence, Clearance prune
60	10 Hickory Shadows	16" Live Oak		Fence, Clearance prune
61	10 Hickory Shadows	13" Live Oak		Fence, Clearance prune
62	10 Hickory Shadows	22" Crepe Myrtle		Hand dig lead from curb to meter, Fence, Clearance prune
63	10 Hickory Shadows	13" Crepe Myrtle	Private tree	Fence
64	10 Hickory Shadows	13" Crepe Myrtle	Private tree	Fence
65	10 Hickory Shadows	4' Sago	Private tree, Not impacted	
66	10 Hickory Shadows	12" Crepe Myrtle	Topped, Private tree	Fence
67	10 Hickory Shadows	13" Crepe Myrtle	Topped	Fence
68	6 Hickory Shadows	12" Crepe Myrtle	Private tree	Fence
69	6 Hickory Shadows	13" Crepe Myrtle		Fence, Clearance prune
70	6 Hickory Shadows	12" Live Oak		Fence, Clearance prune
71	6 Hickory Shadows	3' Palm	Private tree, Not impacted	
72	4 Hickory Shadows	15" Magnolia	50% dieback	Fence, Clearance prune
73	4 Hickory Shadows	7" Crepe Myrtle	Topped, Private tree	Fence
74	4 Hickory Shadows	15" Magnolia	50% dieback, Private, Not impacted	
75	2 Hickory Shadows	33" Live Oak	Thin canopy, 10% dieback	Fence, Clearance prune
76	2 Hickory Shadows	13" Crepe Myrtle	Topped, Private tree, Not impacted	
77	3 Hickory Shadows	17" Red Maple	Topped, Private tree, Not impacted	
78	3 Hickory Shadows	29" Live Oak	Private tree	Fence, Bore waterline, Clearance prune
79	1 Hickory Shadows	11" Magnolia		Fence, Bore waterline, Clearance prune
80	1 Hickory Shadows	18" Crepe Myrtle		Hand dig tap&lead, Fence, Bore waterline, Clearance prune
81	12 Hickory Shadows	3" Redbud	Private tree, Not impacted	
82	12 Hickory Shadows	30' Palm	Private tree, Not impacted	
83	12 Hickory Shadows	18' Palm	Private tree, Not impacted	
84	10 Hickory Shadows	18" Magnolia	Easement tree	Center 30' trenchless construction on trunk of tree
85	12 Hickory Shadows	12" Crepe Myrtle	Easement tree	Center 20' trenchless construction on trunk of tree
86	12 Hickory Shadows	9" Mexican Sycamore	Private tree	Center 20' trenchless construction on trunk of tree
87	1027 Ridgeley	25" Cottonwood	Private tree	Center 30' trenchless construction on trunk of tree
88	1025 Ridgeley	14" Eastern Red Cedar	Easement tree	Center 20' trenchless construction on trunk of tree
89	1027 Ridgeley	17" Pine	Easement tree	Center 30' trenchless construction on trunk of tree
90	1027 Ridgeley	16" Live Oak	Easement tree	Center 30' trenchless construction on trunk of tree



1. THIS TREE PROTECTION PLAN WAS DEVELOPED WITH INFORMATION PROVIDED BY DESIGN ENGINEER IN DRAWINGS DATED MAY 2025. THE PLAN CONSIDERS ALL FITTINGS, VERTICAL OFFSETS AND AREAS OF NECESSARY EXCAVATION. CHANGES MADE TO DESIGN MAY COMPROMISE THE TREE PROTECTION PLAN. REFER SPECIFICATIONS 01535. CONDITION OF EACH TREE IS BASED ON VISUAL EVALUATION AT TIME OF DESIGN. CONDITION AND STRUCTURAL INTEGRITY OF EACH TREE IS NOT GUARANTEED BY DESIGNER AT ANY POINT IN THE FUTURE, AS ENVIRONMENTAL AND MAINTENANCE INFLUENCES ON EACH TREE CAN NOT BE DETERMINED BY DESIGNER.
2. IN AREAS WHERE INDIVIDUAL TREES HAVE NOT BEEN TIED IN BY SURVEY APPROXIMATE LOCATION IS INDICATED ON TYP. ACCURACY OF REPRESENTED LOCATION CANT, AND IS NOT GUARANTEED BY DESIGNER.
3. THE CONTRACTOR'S ARBORIST WILL MARK LOCATIONS OF THE NEW TREES AND OBTAIN APPROVAL BY THE CITY ENGINEER AND CITY FORESTER BEFORE PURCHASING AND PLANTING TREES.

MK.	DESCRIPTION	DATE	DWN.	CHK.

C.N. Koehl 
Urban Forestry, Inc.
210 Stone Bush Ct. • Katy, Texas 77493
281-391-0022 ckoehl@koehlurbanforestry.com

APPROVED:




HDR Engineering Inc. Texas Reg. No. 754
4828 Loop Central Drive, Suite 700 • Houston, Texas 77081
(713) 622-9264 • Fax (713) 622-9265 • www.hdrinc.com

City of Hilshire Village, Texas


Hickory Shadows Drive
Paving, Drainage & Water Line Improvements

TREE PROTECTION PLAN
 SHEET 1 OF 2


Job No.: 10418041	Scale: HORIZ :	SHEET
Date: June, 2025	VERT :	27
Dwn By: G.S. Fuller	One Inch	
Chkd By: N. Le	If above mark does not measure one inch, then this dwg. not to scale	OF 28




TREE PROTECTION FENCING DETAIL A
NOT TO SCALE




TREE PROTECTION FENCING DETAIL B
NOT TO SCALE



DEMO-FORM-POUR WALK WITHOUT DAMAGE TO TREE ROOTS 1" DIAMETER OR LARGER
NOT TO SCALE



ROOT PRUNE FOR WATER, SANITARY, OR STORM LINE
NOT TO SCALE



ROOT PRUNE FOR STREET-CURB & GUTTER - NO OCC
NOT TO SCALE

MK.	DESCRIPTION	DATE	DWN.	CHK.
C.N. Koehl Urban Forestry, Inc. 210 Stone Bush Ct. • Katy, Texas 77493 281-391-0022 ckoehl@koehlurbanforestry.com				
APPROVED:				
 HDR Engineering Inc. Texas Reg. No. 754 4828 Loop Central Drive, Suite 700 • Houston, Texas 77081 (713) 622-9264 • Fax (713) 622-9265 • www.hdrinc.com				
City of Hilshire Village, Texas Hickory Shadows Drive Paving, Drainage & Water Line Improvements				
TREE PROTECTION PLAN SHEET 2 OF 2				
Job No.: 10418041 Date: June, 2025 Dwn By: G.S. Fuller Chkd By: N. Le	Scale: HORZ : VERT : One Inch If above mark does not measure one inch, then this diag. not to scale	SHEET 28 OF 28		